

AREA 640 ACRES
LOCATE WELL CORRECTLY

Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in **QUINTUPLICATE**.

State "C"

(Lease)

Well No. 1, in NE 1/4 of NE 1/4, of Sec. 14, T. 16S, R. 33E, NMPM.

..Pool,

Lea

County.

Well is 660 feet from North line and 660 feet from East line

of Section 14 If State Land the Oil and Gas Lease No. is.....

Drilling Commenced 4-28, 1955 Drilling was Completed 6-8, 1955

Name of Drilling Contractor.....Warren-Bradshaw Exploration Co.

Address..... National Bank of Tulsa Bldg., Tulsa 3, Okla.

Elevation above sea level at Top of Tubing Head.....41.77..... The information given is to be kept confidential until
....., 19.....

OIL SANDS OR ZONES

No. 1, from.....to..... No. 4, from.....to.....

No. 2, from.....to..... No. 5, from.....to.....

No. 3, from.....to..... No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.

No. 2, from.....to.....feet.

No. 3, from.....to.....feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
8 5/8	28	New	300	None	0	0	Surface

MUDDING AND CEMENTING RECORD

MUDGING AND CEMENTING RECORD						
SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
11"	8 5/8	300	250	Haliburton		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Result of Production Stimulation.

...Depth Cleaned Out.....

CORD OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto.

TOOLS USED

Rotary tools were used from 0 feet to 5210 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing, 19.

OIL WELL: The production during the first 24 hours was None barrels of liquid of which % was
was oil; % was emulsion; % water; and % was sediment. A.P.I.
Gravity.

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of
liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico

Northwestern New Mexico

T. Anhy. 1520	T. Devonian	T. Ojo Alamo
T. Salt. 1630	T. Silurian	T. Kirtland-Fruitland
B. Salt. 2720	T. Montoya	T. Farmington
T. Yates. 2795	T. Simpson	T. Pictured Cliffs
T. 7 Rivers. 2960	T. McKee	T. Menefee
T. Queen. 3660	T. Ellenburger	T. Point Lookout
T. Grayburg. 4090	T. Gr. Wash	T. Mancos
T. San Andres. 4460	T. Granite	T. Dakota
T. Glorieta	T.	T. Morrison
T. Drinkard	T.	T. Penn.
T. Tubbs	T.	T.
T. Abo	T.	T.
T. Penn.	T.	T.
T. Miss.	T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
6	190		Lime				
190	1520		Red beds				
1520	2720		Salt & anhy.				
2720	3710		Anhy. & shale				
3710	4090		Anhy. & lime				
4090	4460		Lime & anhy.				
4460	5210		Lime				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far
as can be determined from available records.

June 13, 1955

(Date)

Company or Operator Warren-Bradshaw Exploration Co. Address 202 West Building, Midland, Texas

Name Thomas M. West Position or Title Division Manager

RECORD OF DRILL-STEM TESTS

- 5/7 DST 2960'-3100', open 30 mins., weak blow 15 mins., recovered 15' slight gas cut mud, BHFP 45 lbs., 15 min. shut in pressure 70 lbs.
- 6/2 DST 4985'-5035', open 50 mins., weak blow, recovered 15' slight gas cut mud, 0 lbs. - 0 lbs.
- 6/8 DST 5040'-5210', open 1 hr., fair blow decreasing to 0, recovered 135' of mud, 510' of salt water cut mud, BHFP 120 to 395, 15 min. shut in pressure 1650 lbs.