

DUPLICATE
(Form O-302)
(Revised 4/1/52)

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

August 13, 1957
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the

Cities Service Oil Co. State ND Well No. 1 in A
(Company or Operator) (Unit)
NE 1/4 NE 1/4 of Sec. 15, T. 16S, R. 33E, NMPM., Wildcat Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

This well was drilled to a total depth of 4462'. The 5 1/2" casing was perforated from 4364 to 4394, fractured, swabbed and was found to be non-commercial. It was plugged back to 3984', perforated from 3924-3934 and 3934-3948, fractured, swabbed and pumping equipment installed. The well was pumped from May 6, 1957 to date and only a portion of the lead oil was recovered. This zone is also non-commercial.

It is proposed to plug and abandon the well by reclaiming all possible 5 1/2" casing, loading hole with mud, spot 25 sacks of cement on bottom where 5 1/2" casing is perforated, spot 25 sacks at the point where 5 1/2" casing is shot off, spot 40 sacks cement above the salt section extending up into the 8 5/8" casing at the base and spot 10 sacks in the top of the 8 5/8" casing leaving a 4" pipe 4' above the surface as a marker.

Approved _____, 19____
Except as follows:

*Spot 25 sack plug
@ top of salt.*

Approved
OIL CONSERVATION COMMISSION

By _____

Title Engineer District 1

Cities Service Oil Company
Company or Operator

By [Signature]

Position District Superintendent

Send Communications regarding well to:

Name George M. Geyer

Address Box 97, Hobbs, New Mexico