

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## NOTICE OF INTENTION TO DRILL

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instruction in Rules and Regulations of the Commission.

HOBBS OFFICE

Artesia, New Mexico

April 10, 1941

Place

Date

OIL CONSERVATION COMMISSION.  
Santa Fe, New Mexico.

Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as \_\_\_\_\_

Fullerton Oil Company State \_\_\_\_\_ Well No. 1 in NE SE  
Company or Operator Lease

of Sec. 18, T. 169, R. 33E, N. M. P. M., Wildcat Field, Lea County  
N.

The well is 1980 feet (N.) (☒) of the South line and 660 feet  
(E.) (☒) of the East line of Section 18

(Give location from section or other legal subdivision lines. Cross out wrong directions)

If state land the oil and gas lease is No. B-4282 Assignment No. \_\_\_\_\_

If patented land the owner is \_\_\_\_\_

Address \_\_\_\_\_

If government land the permittee is \_\_\_\_\_

Address \_\_\_\_\_

The lessee is \_\_\_\_\_

Address \_\_\_\_\_

AREA 640 ACRES  
LOCATE WELL CORRECTLY

We propose to drill well with drilling equipment as follows: \_\_\_\_\_

Rotary to 1300' and Cable tools to Total Depth

The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission is as follows: Bond filed with Commission in Santa Fe, New Mexico

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Sacks Cement
13 1/2"	10 3/4"	42	New	1300	Cemented	200
8"	7"	20	New	4200	Cemented	250
						(Two Stage)

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil and gas sand should occur at a depth of about 4400 feet.

Additional information:

**If water encountered in Red Sand will run and cement 8 5/8" Csg at approximately 3300'**

APR 16 1941

Approved \_\_\_\_\_, 19\_\_\_\_

except as follows:

Supper & Supper

Sincerely yours,

Fullerton Oil Company

Company or Operator

By \_\_\_\_\_

Position Superintendent

Send communications regarding well to

Name C. H. SweetAddress Box 187, Artesia, N. M.

OIL CONSERVATION COMMISSION

By \_\_\_\_\_

Title OIL & GAS INSPECTOR