

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed; and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico

(Place)

July 15, 1957

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the Tennessee Gas Transmission Company

State A. A. Kemnitz "B"

Well No. 2 in H

(Unit)

SE NE (Company or Operator) 25 -16-S -35-S Wildcat
 (40-acre Subdivision) 1/4 of Sec. 16, T. 16-S, R. 35-S, NMPM, Wildcat Pool
Lee County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

1. Set cement plug in 5-1/2" Casing from 3900 to 3820'.
2. Cut & pull 3000' 5-1/2" Casing.
3. Fill hole with mud laden fluid 3820' to 3020'.
4. Set cement plug from 3020' to 2980'.
5. Fill hole with mud laden fluid from 2980' to 2680'.
6. Set cement plug from 2680' to 2600'.
7. Fill hole with mud laden fluid from 2600' to 1620'.
8. Set cement plug from 1620' to 1570'.
9. Fill hole with mud laden fluid from 1570' to 320'.
10. Set cement plug from 320' to 270'.
11. Fill hole with mud laden fluid from 270' to 30'.
12. Set cement plug from 30' to 0' and install permanent marker.

Approved....., 19.....
Except as follows:

Tennessee Gas Transmission Company

Company or Operator

By.....

D. P. Dampf

Position.....

District Production Superintendent

Send Communications regarding well to:

Approved
OIL CONSERVATION COMMISSION

By.....

Name.....

Tennessee Gas Transmission Company

203 N. Linan St.

Title.....

Address Hobbs, New Mexico