

MISC INFORMATION

Hole Sizes

12-1/4 inch from surface casing (364') to 1973'

11 inch from 1973 to 4530'

7-7/8 inch from 4530' to TD

Cement Plugs

As per New Mexico Oil Commission records. Well P&A 6/10/62 recovering 2363' of 8-5/8 casing.

| <u>No. Sacks</u> | <u>Depth Set</u> |
|------------------|------------------|
| 10 sx | surface |
| 10 sx | 364' |
| 25 sx | 1,460' |
| 25 sx | 2,368' |
| 25 sx | 4,584' |
| 25 sx | 5,750' |
| 25 sx | 7,750' |
| 25 sx | 10,550' |
| 25 sx | 11,395' |
| 25 sx | 14,230' |
| 30 sx | 14,900' |

Misc Data

| | |
|---------------------------------|-------------------|
| 8-5/8" casing min. | ID 32#/ft = 7.921 |
| 8-5/8" casing cplg | OD = 9.625 |
| 8-5/8" casing | OD = 8.625 |
| 9-5/8" wash pipe | ID = 8.750 |
| 8-5/8" cement type casing patch | OD = 11.250 |
| 8-5/8" cement type casing patch | ID = 8.900 |

RECEIVED

MAR 22 1979

ON COM
1979, 3. 11.