
1	Form	C-1	102				
			-	P		1	NEW

MAEXICO OIL CONSERVATION COM. SSION

Santa Fe, New Mexico



Submit this notice in triplicate to the Oil C A copy will be returned to the sender on w	Conservation Communication will be given	nission or its proper agent before the work specified the approval, with any modifications considered advis itted. The plan as approved should be followed al instructions in the Rules and Regulations of the C	is to begin. sable, or the
rejection by the Commission or agent, os bould not begin until approval is obtain	of the plan submi led. See addition:	itted. The plan as approved should be followed al instructions in the Rules and Regulations of the (, and work commission.
Indic	ate nature of no	tice by checking below:	
OTICE OF INTENTION TO TEST CAS SHUT-OFF	SING	NOTICE OF INTENTION 'TO SHOOT OR CHEMICALLY TREAT WELL	
NOTICE OF INTENTION TO CHANGE	PLANS	NOTICE OF INTENTION TO PULL OR OTHERWISE ALTER CASING	
NOTICE OF INTENTION TO REPAIR V	WELL	NOTICE OF INTENTION TO PLUG WELL	
NOTICE OF INTENTION TO DEEPEN	WELL		
**************************************	rt worth.	lexas Place April 20, 10	45
OIL CONSERVATION COMMISSION,			
Santa Fe, New Mexico. Gentlemen:			
		described below at the	
Company of Sperator	Slease =	Well No. 1	enter N
f Sec. 71 , T. 16 S	R CCE	, N. M. P. M., Wildest	Field,
Lea	County.		
FULL DE FOLLOW INSTRUCTIONS D. 4575. Plussing bas	TAILS OF PR S IN THE RULE ck to 2700	SOPOSED PLAN OF WORK S AND REGULATIONS OF THE COMMISSION feet with heavy mus. Setting guide at 2700 as a bridge. P	lecing
FULL DE FOLLOW INSTRUCTIONS D. 4575. Pluading backliburton plug with 10 acks of cement as a cith heavy mud from top coment the last five feet	TAILS OF PR IN THE RULE of to 2700 ift. 2 x 4 mement pluy of cement i	S AND REGULATIONS OF THE COMMISSION	lacing 11 fill ce and 11 be
FULL DE FOLLOW INSTRUCTIONS D. 4575. Plunging backelliburton plug with 10 acks of cement as a clith heavy mud from top coment the last five feels of in hole. Will set a	TAILS OF PR IN THE RULE of to 2700 ift. 2 x 4 mement pluy of cement i	s and regulations of the commission feet with heavy mud. Setting guide at 2700 as a bridge. P g to protect salt section. Wi plug to within 5 feet of surfa b/o casing set at 1202 feet wi	lacing 11 fill ce and 11 be
FULL DE FOLLOW INSTRUCTIONS D. 4575. Plunging backelliburton plug with 10 acks of cement as a clith heavy mud from top coment the last five feels of in hole. Will set a	TAILS OF PR IN THE RULE of to 2700 ift. 2 x 4 mement pluy of cement i	s and regulations of the commission feet with heavy mud. Setting guide at 2700 as a bridge. P g to protect salt section. Wi plug to within 5 feet of surfa b/o casing set at 1202 feet wi	lacing 11 fill ce and 11 be
FULL DE FOLLOW INSTRUCTIONS D. 4575. Plunging back cliburton plug with 10 is sacks of cement as a cith heavy mud from top coment the last five feet aft in hole. Will sat sequired marker.	TAILS OF PREINTHE RULE ok to 2700 ft. 2 x 4 mement plug of cement g t. The 3 8 4 inch pi	s and regulations of the commission feet with heavy mud. Setting guide at 2700 as a bridge. P g to protect salt section. Wi plug to within 5 feet of surfa b/o casing set at 1202 feet wi	lacing 11 fill ce and 11 be
FULL DE FOLLOW INSTRUCTIONS D. 4575. Plunging back distance of cement as a control to be sacks of cement as a control to be sent in hole. Will set sequired marker.	TAILS OF PR IN THE RULE of to 2700 ift. 2 x 4 mement pluy of cement i	feet with heavy mus. Setting guide at 2700 as a bridge. Posto protect salt section. Without to within 5 feet of surfaction set at 1202 feet withe 4 feet high in cement as the set of the set of the section.	lacing 11 fill ce and 11 be
FULL DE FOLLOW INSTRUCTIONS D. 4575. Plunging back distance of cement as a control to be sacks of cement as a control to be sent in hole. Will set sequired marker.	TAILS OF PREINTHE RULE ok to 2700 ft. 2 x 4 mement plug of cement g t. The 3 8 4 inch pi	s and regulations of the commission feet with heavy mud. Setting guide at 2700 as a bridge. P g to protect salt section. Wi plug to within 5 feet of surfa b/o casing set at 1202 feet wi	lacing 11 fill ce and 11 be
FULL DE FOLLOW INSTRUCTIONS D. 4575. Plunding back elliburton plug with 10 6 sacks of cement as a clith heavy mud from top coment the last five feel eft in hole. Will not sequired marker.	TAILS OF PREINTHE RULE ok to 2700 ft. 2 x 4 mement plug of cement g t. The 3 8 4 inch pi	feet with heavy mus. Setting guide at 2700 as a bridge. Posto protect salt section. Without to within 5 feet of surfaction set at 1202 feet withe 4 feet high in cement as the set of the set of the section.	lacing Il fill ce and Il be he
FULL DE FOLLOW INSTRUCTIONS D. 4575. Plunging back liburton plug with 10 5 sacks of cement as a color top coment the last five feet aft in hole. Will sat sequired marker.	TAILS OF PREINTHE RULE ok to 2700 ft. 2 x 4 mement plug of cement g t. The 3 8 4 inch pi	feet with heavy mus. Setting guide at 2700 as a bridge. Post to protect selt section. Without to within 5 feet of surfactor ceasing set at 1202 feet with 4 feet high in ceasant as the section. By Settion Start Section Sec	lacing Il fill ce and Il be he

Fort Worth, Texas