

DUPLICATE

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELL

RECEIVED  
MAY 26 1944  
HOBBS OFFICE

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-offs, result of plugging or other important operations, even though the work was witnessed by an agent of the commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL	X	REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

Hobbs, New Mexico

Date

OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Shell Oil Company, Inc. State "NM" Well No. 1 in the  
Company or Operator Lease  
SE4/SW4 of Sec. 6 T17-South, R. 33-East, N. M. P. M.,  
East Maljamar Field, Lea County

The dates of this work were as follows:

Notice of intention to do the work was (was not) submitted on Form C-102 on \_\_\_\_\_ 19\_\_\_\_  
and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Plugged back from 4660' to 4350' with cement in two stages. Circulated out 7 sacks on first stage and 14 sacks on second stage. Ran and cemented 4097' 7" casing to 4110 and cemented with 100 sacks 2-19-44. Moved off rotary rig and moved in cable tools. Bailed and swabbed hole dry 3-10-44. Let set for two hours. Test O.K. Drilled out plug and cement. Found first cement with bailer at 4347'. Cement not set. Bailed hole down to 4450'. Bridged from 4450 to 4440'. Plugged back with Calseal from 4449 to 4439 with dump bailer. Plugged back with 17 sacks Incor cement from 4439 to 4319'. Drilled and bailed soft cement to 4388 and drilled 8 feet hard cement. P.B.T.D. 4396'.

Witnessed by O.L. Nuernberger Shell Oil Co., Inc. District Supt.

Subscribed and sworn to before me this

18th day of May, 1944

Notary Public

My Commission Expires April 22, 1945.

My Commission expires

I hereby swear or affirm that the information given above is true and correct.

Name

Position District Superintendent

Representing SHELL OIL COMPANY, Inc.  
Company or Operator

Address Box 1457, Hobbs, N.M.

Remarks:

Roy Yarbrough  
Name  
OIL & GAS INSPECTOR  
Title

...the ... of ...  
...the ... of ...  
...the ... of ...

...the ... of ...  
...the ... of ...  
...the ... of ...

...the ... of ...  
...the ... of ...  
...the ... of ...

...the ... of ...  
...the ... of ...  
...the ... of ...

...the ... of ...  
...the ... of ...  
...the ... of ...

...the ... of ...  
...the ... of ...  
...the ... of ...