

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL	<input checked="" type="checkbox"/>	REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

Dallas, Texas

November 21, 1956

Place

Date

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

Leonard Nichols

State 4

Well No. 5

in the

Company or Operator

Lease

SE 1/4 NW 1/4

of Sec. 8

T. 17S

R. 33E

N. M. P. M.,

Roberts Field

Field,

Lea

County.

The dates of this work were as follows:

Notice of intention to do the work was (was not) submitted on Form C-102 on

19

and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

We ran 364' of 8 5/8" casing in this well and circulated cement to the surface. After waiting for the cement to set we drilled the plug and tests showed a complete water shut-off. Drilling continued.

We ran 4458' of 5 1/2" casing in this well and cemented with 200 sacks of cement. After waiting for the cement to set we tested the results and found a complete water shut-off and that the cement was all out of the casing. Well was perforated 4238-4262, 4350-4384, and 4400-4414. Well was san/raced w/5000 gals oil 5000# sand at 4238, 8000 gals oil 8000# sand at 4348 and 2000 gals oil 1000 # sand at 4400'.

Witnessed by

Name

Company

Title

Subscribed and sworn before me this 23rd

I hereby swear or affirm that the information given above is true and correct.

day of November, 19 56

Name Leonard Nichols

Position Owner

Representing Leonard Nichols
Company or OperatorNotary Public
E. GRISHAM, Notary Public, Dallas County, Texas

My commission expires

Address 901 Mercantile Securities Bldg.,
Dallas 1, Texas

Remarks:

E. J. Fisher
Engineer District 1
Name
Title