

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

X

TO FRACTURE TREAT X

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico

March 26, 1957

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the

State of

Well No. 1 in

Shell Oil Company

1/4 of Sec. 8, T. 17-S, R. 32-E, NMPM, Pool

NE (40-acre Subdivision)

Roberts

Lea

County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

We propose to do the following to increase capacity:

1. Spot 15 bbls. low P. I. (4-8cc) crude on bottom.
2. Shoot w/P.I. Gun at 4364', 4273' & 4247'.
3. Run tubing open-ended w/Lynes packer. Set packer at 4350'.
4. Treat down tubing w/10,000 gallons gelled lease crude w/1# gal. 20-40 mesh sand & sufficient Adomite to obtain 10-15 cc fluid loss. Overflush w/50 BQ. Pull tubing & packer.
5. Run tubing w/hockwall packer. Swab back load & test.
6. Pull tubing & packer.
7. Run tubing w/Lynes straddle packers spaced 35' apart. Set bottom packer at 4302', top packer at 4267' & treat between packers w/10,000 gallons gelled crude as above.
8. Raise packers & set bottom packer at 4260', top packer at 4225' & treat between packers w/10,000 gallons gelled crude as above.
9. Pull tubing & packers.
10. Run tubing, rods & pump. Pump back load & test.

Approved....., 19.....
Except as follows:

Shell Oil Company

By..... Original signed by

B. Nevill

Position.....

B. Nevill

Send to District Office, Engineering

Approved
OIL CONSERVATION COMMISSION

By.....

E. Fischer

Title.....

Name.....

Shell Oil Company

Address.....

Box 1957, Hobbs, New Mexico

