



NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE. If State Land submit 6 Copies

AREA 640 ACRES
LOCATE WELL CORRECTLY
EUGENE TALBERT

Phillips State #1

(Company or Operator) (Lease)
Well No. 1, in NW 1/4 of SW 1/4, of Sec. 16, T. 17S, R. 33E, NMPM.
Maljamar Pool, Lea County.
Well is 660 feet from W line and 1,980 feet from S line
of Section 16. If State Land the Oil and Gas Lease No. is B-2148
Drilling Commenced December 30, 1957 Drilling was Completed January 23, 1958
Name of Drilling Contractor Thomas Drilling Company
Address P. O. Box 2646, Hobbs, New Mexico
Elevation above sea level at Top of Tubing Head 4,214 The information given is to be kept confidential until
Not confidential, 19

OIL SANDS OR ZONES

No. 1, from to No. 4, from to
No. 2, from to No. 5, from to
No. 3, from to No. 6, from to

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from to feet.
No. 2, from to feet.
No. 3, from to feet.
No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
8-5/8	24#	Used	360	Float			WSO
5-1/2	14#	New	4,450				WSO

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
12-1/4	8-5/8	370	200	Displacement		
7-7/8	5-1/2	4,460	200	Displacement		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Treat with 15,000 Gal. plus 15,000# sand.

Result of Production Stimulation IPF - 54 BOPD on 12/64" choke

Depth Cleaned Out

COORD OF DRILL-STEM AND SPECIAL T 3

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 4,460 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing January 29, 1958

OIL WELL: The production during the first 24 hours was 54 barrels of liquid of which 100 % was
was oil; % was emulsion; % water; and % was sediment. A.P.I.
Gravity 39°

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of
liquid Hydrocarbon. Shut in Pressure lbs.
Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):
Southeastern New Mexico Northwestern New Mexico

T. Anhy 1,400	T. Devonian	T. Ojo Alamo
T. Salt 1,530	T. Silurian	T. Kirtland-Fruitland
B. Salt 2,570	T. Montoya	T. Farmington
T. Yates 2,750	T. Simpson	T. Pictured Cliffs
T. 7 Rivers 3,050	T. McKee	T. Menefee
T. Queen 3,700	T. Ellenburger	T. Point Lookout
T. Grayburg 4,078	T. Gr. Wash	T. Mancos
T. San Andres 4,414	T. Granite	T. Dakota
T. Glorieta	T.	T. Morrison
T. Drinkard	T.	T. Penn
T. Tubbs	T.	T.
T. Abo	T.	T.
T. Penn	T.	T.
T. Miss	T.	T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	300		Surface sand, gravel & clay				
300	1,400		Redbeds				
1,400	1,530		Anhydrite				
15,30	2,570		Sand				
2,570	2,750		Anhydrite & lime				
2,750	4,078		Lime & anhydrite with sand stringers				
4,078	4,414		Lime & anhydrite				
4,414	4,460	TD	Lime				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far
as can be determined from available records.

Jan. 30, 1958
(Date)
Company or Operator EUGENE TALBERT Address P. O. Box 2646, Hobbs, New Mexico
Name R. J. Thomas Position or Title Agent