State of New Mexico Submit 3 Copies Form C-103 Energy, Minerals and Natural Resources Department Revised 1-1-89 to Appropriate District Office DISTRICT 1 P.O. Box 1980, Hobbs, NM 88240 WELL API NO. OIL CONSERVATION DIVISION 30-025-01451 DISTRICT 2 P.O. Box 2088 P.O. Drawer DD, Artesia, NM 88210 Indicate Type of Lease Santa Fe, New Mexico 87504-2088 State DISTRICT 3 1000 Rio Brazos Rd., Aztec, NM 87410 6. State Oil & Gas Lease No. B-2148 SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A 7. Lease Name or Unit Agreement Name DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) Caprock Maljamar Unit 1. Type of Well OIL GAS WIW WELL OTHER Х WELL 8. Well No The Wiser Oil Company 32 3. Address of Operator 9. Pool name or Wildcat 207 W. McKay, Carlsbad, NM 88220 505/885-5433 Maljamar Grayburg San Andres 4. Well Location 660 660 East Unit Lette Feet From The Line 17 17S 33E Township NMPM Lea County (Show whether DF, RKB, RT, GR, etc.) Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING COMMENCE DRILLING OPNS. TEMPORARILY ABANDON CHANGE PLANS PLUG AND ABANDONMENT CASING TEST AND CEMENT JOB PULL OR ALTER CASING Deepen & prepare to convert to WIW. OTHER: OTHER: (Clearly state all pertinent details, and give pertinent dates including estimated date of starting any proposed work) SEE RULE 1103. Clean out & deepen to new TD of 4610'. Acidize perfs & OH 4216-4607 w/3000 gal 15% NEFE acid. Set 5 1/2" AD-1 February 1995 tension packer at 4155' w/134 jts 2 3/8" plastic coated tubing. Tested casing to 350 psi for 15 minutes, held good. Casing Integrity Test approved 07/17/95. of my knowledge and belief 07/19/95 SIGNATURE Agent DATE Melanie J. Parker 505/885-5433 TELEPHONE NO. TYPE OR PRINT NAME

(This space for State Use)

ORIGINAL SIGNED BY JERRY SEXTONITLE

CONDITIONS OF APPROVAL IFANY RECT 1 SUPERVISOR

JUL 24 1995