

Submit 3 copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

OIL CONSERVATION DIVISION

310 Old Santa Fe Trail, Room 206
Santa Fe, New Mexico 87503

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Box Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

WELL API NO. 30-025-01457

5. Indicate Type of Lease
STATE ☒ FEE

6. State Oil & Gas Lease No. B-2148

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
Oil Gas
Well Well OTHER WATER INJECTION

2. Name of Operator The Wiser Oil Company

3. Address of Operator 8115 Preston Road, Suite 400, Dallas, TX 75225

4. Well Location
Unit Letter I : 1980 Feet From The South Line and 660 Feet From The West East Line
Section 18 Township 17S 33E NMPM County Lea

10. Elevation (Show whether DF, RKB, GR, etc.)

11. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK	PLUG AND ABANDON	REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON	CHANGE PLANS	COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
PULL OR ALTER CASING		CASING TEST AND CEMENT JOB	
OTHER:		OTHER: Convert to water injection well	X

12. Describe Proposed or Completed Operation (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work)
SEE RULE 1103.

10/23/95 RU. NU BOP. TOH w/2-3/8". PU 4-3/4" bit & 6 - 3-1/2" DC's. RIH w/bit. DC's & 2-3/8" tbg. Tagged fill @ 4436'. Drilling out cmt.

11/07/95 RIH w/5-1/2" Model-R pkr, SN & 2-3/8 tbg. Set pkr @ 4110'. RU Hughes. Acidize perfs 4222-4465 w/2500 gals 15% NEFE acid. Ppd into fm @ rate of 5.5 BPM @ 2500#. ISIP 1800#, 5 min 1400#. Total load to rec 85 bbls. Flwd & swbd back 60 bbls. Unset pkr. TOH & LD 2-3/8" tbg & pkr.

11/08/95 RIH w/5-1/2" AD-1 pkr & 126 jts 2-3/8" plastic coated tbg to 4112'. RU pmp truck. Circ 90 bbls pkr fl. Set pkr @ 4112'. Test pkr to 350# for 15 min, held good.

11/25/95 Initial injection rate 10 BWPD @ 50#.

I hereby certify that the information above is true an complete to the best of my knowledge and belief.

SIGNATURE Betty Epie TITLE Production Administrator DATE 04/25/97

TYPE OR PRINT NAME Betty Epie TELEPHONE NO. (214)265-0080

(THIS SPACE FOR STATE USE)

APPROVED BY CHADLER TITLE DATE MAY 05 1997

CONDITIONS OF APPROVAL, IF ANY:

JCBN

15