

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

# NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

JUL 14 11 48 AM '65

Indicate Type of Lease  
State ☒ Fee ☐

5. State Oil & Gas Lease No.

B-2148

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER- 2. Name of Operator Murphy H. Baxter 3. Address of Operator 1126 Vaughn Building, Midland, Texas 79704 4. Location of Well UNIT LETTER A, 660 FEET FROM THE North LINE AND 660 FEET FROM THE East LINE, SECTION 18 TOWNSHIP 17 RANGE 33 NMPM. 15. Elevation (Show whether DF, RT, GR, etc.) 4216 DF 4205 CL	7. Unit Agreement Name 8. Farm or Lease Name State 18-B 9. Well No. 1 10. Field and Pool, or Wildcat Maljamar (6-SA) 12. County Lea
--	---

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK <input type="checkbox"/>	PLUG AND ABANDON <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	CHANGE PLANS <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	OTHER <input type="checkbox"/>

SUBSEQUENT REPORT OF:

REMEDIAL WORK <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
COMMENCE DRILLING OPNS. <input type="checkbox"/>	PLUG AND ABANDONMENT <input type="checkbox"/>
CASING TEST AND CEMENT JOB <input type="checkbox"/>	OTHER <input checked="" type="checkbox"/> Deepening job

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Commenced deepening on June 26, 1965.

Drilled to 4607 on June 27, 1965.

Set 4" liner from 4339' to 4606', and cemented w/15 sx Latex cement.

Perforated 4402' to 4416 and 4512 to 4522 w/4 jet shots per foot.

Treated perfs 4402' to 4522' w/15,000 gals. refined oil and 30,000# sand.

Re-treated perfs. 4260' to 4319' w/20,000 gals. refined oil and 54,000# sand.

Re-treated perfs. 4238' to 4242' w/10,000 gals. refined oil and 23,000# sand.

Ran 2" EUE tubing and began pumping load oil - 12:30 p.m., 7/4/65.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED W. A. Jensen TITLE Petroleum Engineer DATE July 13, 1965

APPROVED BY \_\_\_\_\_ TITLE \_\_\_\_\_ DATE \_\_\_\_\_

CONDITIONS OF APPROVAL, IF ANY: