

...Depth Cleaned Out.....

REC OF DRILL-STEM AND SPECIAL TESTS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 1394 feet, and from feet to feet.
Cable tools were used from 1394 feet to 4506 feet, and from feet to feet.

PRODUCTION

Put to Producing 4 - 5, 1954
OIL WELL: The production during the first 24 hours was 16 1/2 barrels of liquid of which 100 % was oil; % was emulsion; % water; and % was sediment. A.P.I. Gravity 35.2
GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of liquid Hydrocarbon. Shut in Pressure lbs.
Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico			Northwestern New Mexico		
T. Anhy.	1353		T. Devonian		T. Ojo Alamo
T. Salt	1540		T. Silurian		T. Kirtland-Fruitland
B. Salt	3200		T. Montoya		T. Farmington
T. Yates	3415		T. Simpson		T. Pictured Cliffs
T. 7 Rivers			T. McKee		T. Menefee
T. Queen	3640		T. Ellenburger		T. Point Lookout
T. Grayburg			T. Gr. Wash.		T. Mancos
T. San Andres	4362		T. Granite		T. Dakota
T. Gorieta			T.		T. Morrison
T. Drinkard			T.		T. Penn.
T. Tabbs			T.		T.
T. Abo			T.		T.
T. Penn.			T.		T.
T. Miss.			T.		T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	450	450	Celiche & sand	3225	3355	130	Anhyd.
450	765	315	Red bed & shells	3355	3390	35	" & shale
765	780	15	Anhyd.	3390	3420	30	"
780	1353	573	Red shale	3420	3445	25	" & red shale
1353	1540	187	Anhyd.	3445	3595	150	Anhyd.
1540	1635	95	Salt	3595	3600	5	Lime
1635	1650	15	Anhyd.	3600	3610	10	Anhyd.
1650	1710	60	Salt	3610	3645	35	" broken
1710	1755	45	" & potash	3645	3650	5	"
1755	2480	725	Salt	3650	3665	15	Lime
2480	2505	25	Anhyd.	3665	3725	60	Anhyd.
2505	2590	85	" & shale	3725	3780	55	" & lime
2590	2670	80	Anhyd.	3780	4012	232	" & shale
2670	2755	85	Broken anhyd.	4012	4433	421	Lime
2755	2790	35	Anhyd.	4433	4443	10	Sand - hard
2790	2890	100	" & shale	4443	4506	63	Lime
2890	2955	65	Anhyd.				
2955	3030	75	" & shale				
3030	3085	55	Anhyd.				
3085	3115	30	" & blue shale				
3115	3205	90	Anhyd.				
3205	3225	20	" & blue shale				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

June 26, 1954

(Date)

Company or Operator Carper Drilling Company, Inc. Address Artesia, New Mexico
Name J. Marshall Ray Position or Title Vice-Pres.