

OIL CONSERVATION COMMISSION

SANTA FE, NEW MEXICO

TRIPPLICATE
 Miscellaneous Reports on Wells

RECEIVED

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below.

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF	X	REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL			

April 26, 1952

Date

Hobbs, New Mexico

Place

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the.....

Horsting Oil Company Phillips-State Well No. 1 in the
 Company or Operator Lease

SW 1/4 NE 1/4 of Sec. 20 T. 17S R. 33E N. M. P. M.,
 Wildcat Field Lee County.

The dates of this work were as follows: April 24, 1952

Notice of intention to do the work was (was not) submitted on Form C-102 on..... 19.....

and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Upon Form C-101, approved January 24, 1952, we specified setting and cementing 4500' of 5 1/2" casing. At total depth of 4197', however, hole caved so badly we found it necessary to run and cement a string of 7" casing. This was done on April 17, 1952 and same was cemented at depth of 4050' with 50 sack of neat cement and 200 sack of 4% jel cement. Halliburton pump truck broke down momentarily when plug was 444' off bottom. When pump was repaired, cement had set. Calculated left 92 sack in casing. Drilled same out and tested casing OK, after 72 hrs.

Witnessed by Name Roach & Shepard Company Co-owner Title
 Clarence Roach

Subscribed and sworn before me this.....

I hereby swear or affirm that the information given above is true and correct.

..... day of....., 19.....

Name *Charles P. Miller*

Position Agent

Notary Public

Representing Horsting Oil Company
Company or Operator

My commission expires.....

Address Chicago, Illinois.

Remarks:

Ray Quakrogh
 Name
 Title