NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

•

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		Notice of Intention to Temporarily Abandon Wel	L	NOTICE OF INTENTION TO DRILL DEEPER	
OTICE OF INTENTION O PLUG WELL	x	Notice of Intention to Plug Back		Notice of Intention to Set Liner	
OTICE OF INTENTION O SQUEEZE	1	Notice of Intention to Acidize		Notice of Intention to Shoot (Nitro)	
OTICE OF INTENTION O GUN PERFORATE		Notice of Intention (Other)		Notice of Intention (Other)	
IL CONSERVATION COM ANTA FE, NEW MEXICO	MISSION	TEXACO Ine. P. O. Box 352, Mid (Place)	land, Texa	18 Jun	17, 1960
entlemen:		(Place)		(De	ate)
		certain work as described below M. Arreguy		7	•
(Compe	iny or Operator	M. Arreguy		Well No	in
(40-acre Subdivision)	Sec	, T. , R. 34 4		Wildcat	****
Cut off 5-1/2" 0 Spot 25 sx. from Spot 40 sx. from	(FOLLOW nd aband 10,450' (.D. casi: .50' balo .8000' tz	L DETAILS OF PROPOSI INSTRUCTIONS IN THE R IN subject well as for to 10,200' inside 5-1 ng at approx 8870', a W to 50' above top of 8100'.	ULES AND R	EGULATIONS)	
Gut eff 5-1/2" 0 Spot 25 sx. from Spot 40 sx. from Spot 40 sx. from Spot 40 sx. from Spot 40 sx. from Cut 9-5/8" 0.D. Spot 60 sx. from	(FOLLOW nd aband 10,450' f .D. easin 50' belo 6000' to 4550' to 4550' to 50' belo 50' belo	INSTRUCTIONS IN THE R In subject well as for to 10,200' inside 5-1 ng at approx 8870', a W to 50' above top (0 8100'.	ULES AND R 11.0WS: /2" 0.D. (2" 0.D. (2" 0.D. (2" 0.D. (1" 0.D. (0.D. cash 6 cover sen f cut off	EGULATIONS) Casing. Casing. Casing. Ing seat) He if possible. 9-5/8" CD easing	
Gut eff 5-1/2" 0 Spot 25 sx. from Spot 40 sx. from Spot 40 sx. from Spot 40 sx. from Spot 40 sx. from Cut 9-5/8" 0.D. Spot 60 sx. from Spot 60 sx. from Spot 75 sx. from Spot 20 sx. surfu regulations.	(FOLLOW nd aband 10,450' f .D. easin 50' belo 6000' to 4550' to 4550' to 50' belo 50' belo	INSTRUCTIONS IN THE R an subject well as for te 10,200' inside 5-1 ng at apprex 8870', a pw to 50' above top of a 8100'. 7350'. 6100'. 7350'. 6100'. 7350', (over 9-5/8" approx 1265', and r w to 50' above top of 400' (over 13-3/8" 0.D. ca install 4" marker e	ULES AND R 110WS: /2" 0.D. (and recover of cut off 0.D. casing scover sem f cut off .D. casing sing. xtending 4	EGULATIONS) casing. " Same. casing. ing seat) me if possible. 9-5/8" CD easing ; seat). " above ground as	
Gut eff 5-1/2" 0 Spot 25 sx. from Spot 40 sx. from Spot 40 sx. from Spot 40 sx. from Spot 40 sx. from Cut 9-5/8" 0.D. Spot 60 sx. from Spot 60 sx. from Spot 75 sx. from Spot 20 sx. surfu regulations.	A shend 10,450' f .D. easin 50' belo 8000' to 7250' to 6000' to 4550' to belo 300' to arines in the plug,	INSTRUCTIONS IN THE R an subject well as for te 10,200' inside 5-1 ng at apprex 8870', a pw to 50' above top of a 8100'. 7350'. 6100'. 7350'. 6100'. 7350', (over 9-5/8" approx 1265', and r w to 50' above top of 400' (over 13-3/8" 0.D. ca install 4" marker e	ULES AND R 110WS: /2" 0.D. (and recover of cut off 0.D. casing scover sem f cut off .D. casing sing. xtending 4	EGULATIONS) Casing. Casing. Casing. Ing seat) He if possible. 9-5/8" CD easing	
Gut eff 5-1/2" 0 Spot 25 sx. from Spot 40 sx. from Spot 40 sx. from Spot 40 sx. from Spot 40 sx. from Cut 9-5/8" 0.D. Spot 60 sx. from Spot 60 sx. from Spot 75 sx. from Spot 20 sx. surfu regulations.	A shend 10,450' f .D. easin 50' belo 8000' to 7250' to 6000' to 4550' to belo 300' to arines in the plug,	INSTRUCTIONS IN THE R an subject well as for te 10,200' inside 5-1 ng at apprex 8870', a pw to 50' above top of a 8100'. 7350'. 6100'. 7350'. 6100'. 7350', (over 9-5/8" approx 1265', and r w to 50' above top of 400' (over 13-3/8" 0.D. ca install 4" marker e	ULES AND R 110WS: /2" 0.D. (and recover of cut off 0.D. casing scover sem f cut off .D. casing sing. xtending 4	EGULATIONS) casing. " same. casing. ing seat) m if possible. 9-5/8" CD easing: seat). " above ground as 0 Inc.	
Gut eff 5-1/2" 0 Spot 25 sx. from Spot 40 sx. from Spot 40 sx. from Spot 40 sx. from Spot 40 sx. from Cut 9-5/8" O.D. Spot 60 sx. from Spot 60 sx. from Spot 75 sx. from Spot 20 sx. surfi regulations.	(Follow nd aband 10,450' .D. easin 50' belo 6000' to 4550' to 6000' to 4550' to 50' belo 300' to arface in to plug,	INSTRUCTIONS IN THE R an subject well as for te 10,200' inside 5-1 ng at apprex 8870', a pw to 50' above top of a 8100'. 7350'. 6100'. 7350'. 7	ULES AND R Allows: /2" O.D. o md recover af cut off O.D. casing scover sam f cut off .D. casing sing. xtending 4 TEXAC	EGULATIONS) casing. " same. casing. ing seat) m if possible. 9-5/8" CD easing: seat). " above ground as 0 Inc.	s per MNOCC
Gut eff 5-1/2" 0 Spot 25 sx. from Spot 40 sx. from Spot 40 sx. from Spot 40 sx. from Spot 40 sx. from Cut 9-5/8" 0.D. Spot 60 sx. from Spot 60 sx. from Spot 60 sx. from Spot 40 sx. st sx Spot 20 sx. surf	(Follow nd aband 10,450' .D. easin 50' belo 6000' to 4550' to 6000' to 4550' to 50' belo 300' to arface in to plug,	INSTRUCTIONS IN THE R an subject well as for te 10,200' inside 5-1 ng at apprex 8870', a pw to 50' above top of a 8100'. 7350'. 6100'. 5 6100'. 5 6100'. 5 6100'. 5 6100'. 6 6100'. 6 6100'. 6 6100'. 6 6100'. 6 6100'. 6 6100'. 6 6100'. 6 6100'. 6 6100'. 7350'. 6 6100'. 7350'. 7350'. 6 6100'. 7350'	ULES AND R Llows: /2" O.D. o md recover af cut off O.D. casing sing. recover sam f cut off .D. casing sing. recover conditioned 	EGULATIONS) casing. r same. casing. ing seat) m if possible. 9-5/8" (D easing seat). " above ground as 0 Inc. company of Operator t Dignrict Superi	s per MNOCC