

THIS CRUISE
No. 069053

FAIRBANKS DISTRICT #2

WELL LOG REPORT OF ABANDONMENT

well plugged and abandoned as follows:

Total depth of well - 13,513 feet.

Cement plug from 13,513' to 13,350'

Baker Model C open hole bridging plug at 13,350'

5-1/2" casing set at 13,350'

Casing perforated 13,228' to 13,246' and 13,272' to 13,288'

Baker Model K bridging plug at 13,185'

Casing perforated 13,010' to 13,020'

Squeezed perforations 13,010' to 13,020' with 25 sacks cement, reversed out 10 sacks

Drilled out cement to 13,002'

Casing perforated 12,990' to 13,000'

Baker cast iron bridging plug at 12,950' with 18' of cement on top of plug.

Second bridging plug at 11,322'

Casing perforated 11,270' to 11,300'

Squeezed perforations 11,270' to 11,300' with 64 sacks cement, reversed out 20 sacks

Baker cast iron bridging plug at 10,125'

Casing perforated 10,050' to 10,105'

Cemented with 25 sacks, reversed out 5 sacks, top cement at 9900'.

Baker bridging plug at 9875'.

Casing perforated 9825' to 9850'

First plug from 5750 to 5350' with 100 sacks Lone Star cement. Plug in place 11:10 A. M.

2-15-53.

Second Plug from 4631 to 4431 with 80 sacks Lone Star cement. Plug in place 12:10 P. M.

2-15-53.

Third Plug from 30' to surface with 100 sacks Lone Star cement. Plug in place 4:15 P. M.

2-15-53.

Marker placed in accordance with regulations.

C. M. Gier