

OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

SEP 6 - 1945

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-off, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the Commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	X		

Roswell, New Mexico

Feb. 26, 1945

Place

Date

OIL CONSERVATION COMMISSION,
SANTA FE, NEW MEXICO.
Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the _____
The Vickers Petroleum Co., Inc. State _____ Well No. 1 in the _____
 _____ Company or Operator Lease _____
C Lot 8 of Sec. 2, T. 16S, R. 34E, N. M. P. M.,
Wildcat Lea Field, _____ County.

Feb. 15 to Feb. 23, 1945

The dates of this work were as follows:

Notice of intention to do the work was (was not) submitted on Form C-102 on Feb. 15 1945
 and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

We plugged the bottom of the hole with gravel to a depth of 5237'. Then set a 10 sack cement plug; the hole was then filled with mud to a depth of 2950' where another 10 sack cement plug was set; the hole was then filled with mud to a depth of 1830' where another 10 sack cement plug was set. The upper 414 feet of 8 5/8" casing was pulled and the hole filled with mud to a depth of 250' where another 10 sack cement plug was set. The hole was then filled with mud to a surface and capped with cement and a metal marker 4' above the ground was set.

Witnessed by Amos L. Bunte **The Vickers Petroleum Co. - Geological Engineer**
 Name Company Title

Subscribed and sworn before me this 26th

I hereby swear or affirm that the information given above is true and correct.

_____ day of February, 1945

Name Amos L. Bunte

Position Geological Engineer

Representing The Vickers Petroleum Co., Inc.
 Company or Operator

My commission expires

October 3, 1945
Oct 24, 1945

Address 201 W-K-H Bldg., Wichita, Kans.

Remarks:

Ray Yurkovich
 Name
 Oil & Gas Inspector
 Title