


YATES PETROLEUM CORPORATION
York ARQ #1
Section 12-T16S-R34E
Lea County, New Mexico

SUNDRY NOTICE CONTINUED:

9229'). Circulated. Picked up drill pipe. TIH from 9624-10454'. Circulate and condition mud. Picked up drill pipe and TIH.
4-22-98 - TD 13269'. Circulate and condition mud. Made 2815' in 13-1/4 hours. Picked up drill pipe and TIH from 10454-11531'. Circulate and condition gas cut mud. Picked up drillpipe and wash in hole from 11531-12340'. Circulate and condition gas cut mud. Picked up drillpipe and wash in hole from 12340-13269'. Condition mud. Reached TD at 3:00 AM 4-22-98.
4-23-98 - TD 13269'. Logging. Circulate and condition mud. TOOH - SLM 13272.64'. Rigged up loggers and logged well.
4-24-98 - TD 13269'. Laying down drill pipe. Rigged loggers down. TIH with drill pipe. Tagged bridge at 12793'. Picked up kelly. Washed to bottom with 38' of fill. Circulate. Made 12 stand short trip with 10' of fill. Circulated. Laying down drillpipe.
4-25-98 - Ran 323 joints of 5-1/2" 17# casing as follows: 78 joints of 5-1/2" 17# M-95 8rd LT&C (3188.96'); 70 joints of 5-1/2" 17# N-80 8rd LT&C (2898.37'); 55 joints of 5-1/2" 17# J-55 8rd LT&C (2248.46'); 76 joints of 5-1/2" 17# L-80 8rd LT&C (3121.04') and 44 joints of 5-1/2" 17# M-95 8rd LT&C (1824.19') (Total 13281.02') of casing set at 13269'. Float shoe set at 13269'. Float collar set at 13236'. Bottom marker set at 13041-13062' and top marker set from 10080-10101'. Pumped 500 gallons Mud Clean and 500 gallons of Surebond ahead of 380 sacks 65-35-6, 7/10% FL52 and 1/4#/sack celloflake (yield 1.99, weight 12.4). Tailed in with 900 sacks Super Modified C, 4/10% FL52, 4/10% FL25 and 1/4#/sack celloflake (yield 1.66, weight 13.0). PD 2:00 AM 4-25-98. Bumped plug to 2000 psi for 3 minutes, OK. NOTE: Displaced casing with 10# brine water. WOC. Released rig at 7:00 AM 4-25-98.

Waiting on completion unit.


Rusty Kleid

Operations Technician
April 27, 1998