

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	<input checked="" type="checkbox"/>	NOTICE OF INTENTION (OTHER) <b>Sandoff Frac</b>	<input checked="" type="checkbox"/>	NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICO**Hobbs, New Mexico**  
(Place)**March 5, 1960**  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

**Sinclair Oil & Gas Company** **Queen Unit** Well No. **2** in **D**  
(Company or Operator) (Unit)  
**NW**  $\frac{1}{4}$  **NW**  $\frac{1}{4}$  of Sec. **19**, T. **16**, R. **34**, NMPM., **Kennits Wolfcamp** Pool  
(40-acre Subdivision)  
**Lee** County.

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

**PROPOSE TO:** Set Cast Iron Bridge Plug at 9800' in 5-1/2" OD Casing with cement plug from 9800' to 9790'.  
Shoot off and pull 5-1/2" OD Casing from approximately 9300'.  
Fill hole with heavy mud (On DST there were no shows of oil, gas or water from 9300' to 4600').  
Set 25 sack cement plug in top of 5-1/2" OD Casing from 9270' to 9330'.  
Set Cast Iron Bridge Plug in bottom of 9-5/8" OD Casing at 4600' with cement plug on top of bridge plug from 4600' to 4590'.  
Recomplete well in the Queen Zone by perforating 9-5/8" OD casing from 3990' to 3958' and treating with 500 gallons mud acid and 15,000 gals & 15,000 lbs sandfrac treatment.

(Note: 9-5/8" OD Casing set at 4600'.)

Approved....., 19.....  
Except as follows:**Sinclair Oil & Gas Company**  
Company or Operator

By.....

Position..... **Dist. Supt.**

Send Communications regarding well to:

Approved  
OIL CONSERVATION COMMISSION

By.....

Name..... **Fred Burns**

Title.....

Address..... **520 E Broadway, Hobbs, N.M.**

Origins: OCC; of State Land Office; of State Oil &amp; Gas Division; of Cities Service; Shell Oil; Shell Oil