

NO. OF COPIES RECEIVED

DISTRIBUTION

SANTA FE

FILE

U.S.G.S.

LAND OFFICE

OPERATOR

## NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103  
Supersedes Old  
C-102 and C-103  
Effective 1-1-65

5a. Indicate Type of Lease

State ☒Fee ☐

5. State Oil &amp; Gas Lease No.

OG-180

## SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.  
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER -		7. Unit Agreement Name
2. Name of Operator <b>Union Oil Company of California</b>		8. Farm or Lease Name <b>Lea "E" State</b>
3. Address of Operator <b>P. O. Box 671 - Midland, Texas 79701</b>		9. Well No. <b>1</b>
4. Location of Well UNIT LETTER <b>G</b> , <b>1980</b> FEET FROM THE <b>North</b> LINE AND <b>1980</b> FEET FROM THE <b>East</b> LINE, SECTION <b>21</b> TOWNSHIP <b>16 South</b> RANGE <b>34 East</b> NMPM.		10. Field and Pool, or Wildcat <b>Kennitz Cisco</b>
15. Elevation (Show whether DF, RT, GR, etc.) <b>4107' S.C.F.</b>		12. County <b>Lea</b>

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data  
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐TEMPORARILY ABANDON ☐PULL OR ALTER CASING ☐PLUG AND ABANDON ☒CHANGE PLANS ☐OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐COMMENCE DRILLING OPNS. ☐CASING TEST AND CEMENT JOB ☐OTHER ☐ALTERING CASING ☐PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

Move in and rig up casing pulling unit.

Set CI Bridge Plug at approximately 11,400'.

Run tubing, circulate hole with 9.5 ppg salt water mud, pull tubing.

Spot Plug No. 1 11,400' to 11,120' in 5-1/2" OD Casing with 35 sx cement.

Free-point 5-1/2" OD Casing and cut casing at approximately 6000', pull and lay down casing.

Spot Plug No. 2 with 50 sx cement in and out of 5-1/2" OD Casing stub and 7-7/8" open hole.

Spot Plug No. 3 from 5700' to 5600' with 50 sx cement in 7-7/8" open hole.

Spot Plug No. 4 in 7-7/8" open hole and bottom of 8-5/8" OD Casing from 4580' to 4480' with 50 sx cement.

Spot Plug No. 5 in 8-5/8" OD Casing from 1800' to 1700' with 50 sx cement.

Spot Plug No. 6 in 11-3/4" OD Casing from 30' to surface with 20 sx cement.

Cut off well heads and weld 1/2" steel plate on casing.

9.5 ppg drilling mud to be placed between cement plugs.

Install 4" pipe marker with permanent location, according to N.M.O.C.C. regulations.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED J. R. Hughes TITLE District Drilling Supt.

DATE January 6, 1976

APPROVED BY John Sexton

TITLE Dist. L. Supt.

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY: