

# NEW MEXICO OIL CONSERVATION COMMESSION

Santa Fe, New Mexico

1000 MM CO MM 10 49

## WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE.

If State Land submit 6 Copies

(Company or Operator)  (No. 1. in SW. 40 SW. 44, of Sec. 21. T.=16-88. R.=34-88. NM  Kessaitz Wolfersop Pool, Las Co.  (A. 1 is 660 feet from South line and 660 feet from West.  (It State Land the Oil and Gest Lesse No. is Quantile.  (It State Land the O		E WELL COR			on Come	15		State "C"	
Island   Continued   Continu		(	Company or Ope	rator)	_			(Lease)	
I is	-								
LIT State Land the Oil and Graz Lease No. is. OGm378.  Ling Commenced. March 17, 19.58. Drilling was Completed. May 9, 19.58. Drilling Contractor Entry McGes City, Oklahoma  The information given is to be kept confidential of the information given is to				_					
ling Commenced. March 17, 19.58. Drilling was Completed. May 9, 1952  no of Drilling Contractor. Esty-McGos City, Oklahoma  Driss. Oklahoma City, Oklahoma  AliQa3 The information given is to be kept confidential  19.  OIL SANDS OR ZONES  1, from 10745 to 10773 No. 4, from to No. 5, from to No. 5, from to No. 6, from No. 6, fr									* * *
Oklahoma City, Oklahoma  Oklahoma City, Oklahoma  Oklahoma City, Oklahoma  Vation above sea level at Top of Tubing Head									
OKLANCES City, Oklahoma City, Oklahoma  Aution above sea level at Top of Tubing Head									
OIL SANDS OR ZONES  1, from 10745 to 10773 No. 4, from to 2, from to No. 5, from to No. 6, from		•					· ·		
OIL SANDS OR ZONES  1, from 10745 to 10773 No. 4, from to No. 5, from to No. 5, from to No. 6, feet.  2, from 10799 to 10808 feet.  3, from to feet.  CASING RECORD  SIZE WEIGHT NEW OR AMOUNT SENSE PULLED FROM PERFORATIONS FURFOSE NO. 8, 1/2 17 New 10900 RONCO CALIBE  MUDDING AND CEMENTING RECORD  MUDDING SIZE OF WHERE NO. 8, 26, 26 Plant SET OF CEMENT USED GRAVITY MUD USED TO PURE SET OF CEMENT USED GRAVITY MUD USED TO PURE SET OF CEMENT USED GRAVITY MUD USED TO PURE SET OF CEMENT USED GRAVITY MUD USED TO PURE SET OF CEMENT USED GRAVITY MUD USED TO PURE SET OF CEMENT USED GRAVITY MUD USED TO PURE SET OF CEMENT USED GRAVITY MUD USED TO PURE SET OF CEMENT USED APPLIES OF CEMENT SET OF CEMENT USED GRAVITY MUD USED TO PURE SET OF CEMENT SET			=						
OIL SANDS OR ZONES  1, from			=			110.3	The is	nformation given is	to be kept confidential u
1, from 10745 to 10773 No. 4, from to 2, from to No. 5, from to No. 5, from to No. 6, from No	,	,		, 19	<b></b>				
2, from					оп	L SANDS OR ZO	nes		
IMPORTANT WATER SANDS  lude data on rate of water inflow and elevation to which water rose in hole.  1, from 10799 to 10808 feet.  2, from to feet.  3, from to feet.  4, from to feet.  CANING RECORD  SIZE WEIGHT NEW OR AMOUNT SHOE PULLED FROM FERFORATIONS FURFOSE  3, 78	. 1, from	107	45	to	10773	No. 4,	from	***************************************	.to
IMPORTANT WATER SANDS	2, from			to		No. 5,	from		.to
Lude data on rate of water inflow and elevation to which water rose in hole.  1, from	3, from			to		No. 6,	from	*****************************	.to
Lude data on rate of water inflow and elevation to which water rose in hole.  1, from					WDAE		GANDE		
1, from 10799 to 10808 feet. 2, from to feet. 3, from to feet. 4, from to feet.  CASING RECORD  CASING RECORD  SIZE WEIGHT NEW OR AMOUNT SHOE PULLED FROM PERFORATIONS FURPOSE  3 /8 54.5 & 48 New 2 339 TP Guide  5 /8 32 & 24 New & Used 4546 Ploat 1/2 17 New 10900 HOWCO Guide  MUDDING AND CEMENTING RECORD  MUDDING AND CEMENTING RECORD  MUDDING AND CEMENTING RECORD  METHOD MUDDING AND CEMENT USED GRAVITY AMOUNT OF MUD USED  7 1/2* 13 3/8 353 350 Pump & Plug	elude data	on rate of w	ater inflow an	d elevat					
2, from to feet.  3, from to feet.  4, from to feet.  CASING RECORD  CASING RECORD  SIZE WEIGHT NEW OR USED AMOUNT SHOE PULLED FROM PERFORATIONS PURPOSE  3 2/8 54.5 4.8 Rew 339 TP Guide  5/8 32 2 2 New & Used 4546 Float.  1/2 17 Rew 10900 HOWCO Guide  MUDDING AND CEMENTING RECORD  MUDDING AND CEMENTING RECORD  METHOD MUD GRAVITY AMOUNT OF HOLE CASING SET OF CEMENT USED GRAVITY MUD USED  7 1/2* 13 3/8 353 350 Pump & Plug								feet,	***************************************
CASING RECORD  CASING RECORD  SIZE WEIGHT NEW OR AMOUNT SHOE PULLED FROM PERFORATIONS PURPOSE  3 2/8 54.5 8 48 New 339 TP Guide  5/8 32 8 24 New & Used 4546 Float  1/2 17 New 10900 HONCO Guide  MUDDING AND CEMENTING RECORD  SIZE OF SIZE OF CASING SET OF CEMENT USED GRAVITY AMOUNT OF MUD USED  7 1/27 13 3/8 353 350 Pump & Plug  18 8 5/8 4557 2050 Pump & Plug									
CASING RECORD  CASING RECORD  SIZE WEIGHT NEW OR AMOUNT SHOE PULLED FROM PERFORATIONS PURPOSE  3 2/8 54.5 8 48 New 339 TP Guide  5/8 32 8 24 New & Used 4546 Float  1/2 17 New 10900 HONCO Guide  MUDDING AND CEMENTING RECORD  SIZE OF SIZE OF CASING SET OF CEMENT USED GRAVITY AMOUNT OF MUD USED  7 1/27 13 3/8 353 350 Pump & Plug  18 8 5/8 4557 2050 Pump & Plug	. 3, from				to	**********************		feet	~~~~~~~
SIZE PER FOOT USED AMOUNT SHOE PULLED FROM PERFORATIONS PURPOSE  3 3/8 54.5 & 48 New 339 TP Guide  5/8 32 & 24 New & Used 4546 Float  1/2 17 New 10900 HOWCO Guide  MUDDING AND CEMENTING RECORD  MIZE OF SIZE OF WHERE NO. SACKS OF CEMENT USED GRAVITY AMOUNT OF MUD USED  7 1/2* 13 3/8 353 350 Pump & Plug  18 8 5/8 4557 2050 Pump & Plug	•								
SIZE WEIGHT NEW OR USED AMOUNT SHOE PULLED FROM PERFORATIONS PURPOSE  3 3/8 54.5 & 48 New 330 TP Guide  5/8 32 & 24 New & Used 4546 Float  1/2 17 New 10900 HOWCO Guide  MUDDING AND CEMENTING RECORD  SIZE OF SIZE OF WHERE NO. SACES METHOD WUD GRAVITY AMOUNT OF HOLE CASING SET OF CEMENT USED GRAVITY MUD USED  7 1/2* 13 3/8 353 350 Pump & Plug  1* 8 5/8 4557 2050 Pump & Plug	,								
SIZE FEE FOOT USED AMOUNT SHOE PULLED FROM PERFORATIONS PURPOSE  3 3/8 54.5 4.8 New 330 TP Guide  5/8 32 4.24 New & Used 4546 Float  1/2 17 New 10900 HOWCO Guide  MUDDING AND CEMENTING RECORD  SIZE OF SIZE OF WHERE NO. SACKS OF CEMENT USED MUD GRAVITY MUD USED  7 1/24 13 3/8 353 350 Pump & Plug  1 2 3/8 353 2050 Pump & Plug  1 2 3/8 353 2050 Pump & Plug  1 3 3/8 353 2050 Pump & Plug	<del></del>	<u> </u>	ı					<u> </u>	
S	SIZE				AMOUNT			PERFORATIO	NS PURPOSE
MUDDING AND CEMENTING RECORD  SIZE OF SIZE OF WHERE NO. SACES METHOD MUD AMOUNT OF HOLE CASING SET OF CEMENT USED GRAVITY MUD USED  7 1/2* 13 3/8 353 350 Pump & Plug 1* 8 5/8 4557 2050 Pump & Plug	3 3/8	54.5 8	. 48 B	DV	339	TP Guide			
MUDDING AND CEMENTING RECORD  SIZE OF SIZE OF CASING SET OF CEMENT USED MUD GRAVITY MUD USED  7 1/2* 13 3/8 353 350 Pump & Plug 1* 8 5/8 4557 2050 Pump & Plug	5/8	32 &					4_		
SIZE OF SIZE OF WHERE NO. SACES METHOD MUD AMOUNT OF HOLE CASING SET OF CEMENT USED GRAVITY MUD USED  7 1/2" 13 3/8 353 350 Pump & Plug 1" 8 5/8 4557 2050 Pump & Plug	1/2	1	No.		10900	HURLO GUI			
SIZE OF SIZE OF WHERE NO. SACES METHOD MUD AMOUNT OF HOLE CASING SET OF CEMENT USED GRAVITY MUD USED  7 1/2" 13 3/8 353 350 Pump & Plug 1" 8 5/8 4557 2050 Pump & Plug									
HOLE CASING SET OF CEMENT USED GRAVITY MUD USED  7 1/2** 13 3/8 353 350 Pump & Plug 1** 8 5/8 4557 2050 Pump & Plug	<del></del> -	1	<del></del>	T	<u> </u>		NG RECORD		
1" 8 5/8 4557 2050 Pump & Plug	HOLE HOLE			OF	O. SACKS CEMENT				AMOUNT OF MUD USED
	7 1/2"	13 3/8	353	1	350	Pump & Pl	ng		
7/8" 5 1/2 10886 300 Pump & Plug	10	8 5/8	4557	<del> </del>	2050				
	7 7/8"	5 1/2	10886		300				
			(Record	the Pro	ocess used, No	o. of Qts. or Gal	s. used, interva	l treated or shot.)	
(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)	Per	r 281 (	10748-107	70) v	/5 lets 1	er foot.	cidised w	1th 2000 gal	lons retarded act
(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)  Perf 28' (10748-10770) w/5 jets per foot. Acidised with 2000 gallons retarded ac	••••••••••	••••••	***************	,	. 420	******************			***************************************
	<u>-</u>			,			***************************************	•	
Perf 28' (10748-10770) v/5 jets per foot. Acidized with 2000 gallons retarded ac	• • • • • • • • • • • • • • • • • • • •								
Perf 28' (10748-10770) v/5 jets per foot. Acidized with 2000 gallons retarded ac	sult of Pro	duction Stim	ulation	Natur	al flow	of 10.4 BO	on 20/64"	choke during	g first hour.
	sult of Pro	duction Stim	ulationd flow in	Natur <b>cres</b> s	ral flow o	of 10.4 BO (	on 20/64" urs on 20/	choke during	g first hour.

### CORD OF DRILL-STEM AND SPECIAL T

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

#### TOOLS USED

									feet to	
Cable tools	were da	cu mom	***************************************	<b>1</b> 00.			na mon	•••••	eet to	Icet.
<b>.</b>						UCTION				
Put to Pro-			<b>13</b>		-					
OIL WEL			÷						uid of which	_
	was	oil;	%	was em	ulsion;	•••••	% wate	r; and	% was	sediment. A.P.I.
	Gra	vity	43	•••••	•••••••••••••••••••••••••••••••••••••••					
GAS WEL	L: The	productio	n during the first	24 hour	rs was		M,C.F. p	lus	••••••	barrels of
	liqu	iid Hydroc	arbon. Shut in Pre	ssure	lb	<b>3.</b>				
Length of	Time Si	nut in				_				
	N .						CE WEE	H GROGE	APHICAL SECTION	OF COAME.
FLEE	SE IND	MCAIE B	Southeastern N			NEURMAN	CE WII	n GEOGR	Northwestern New	-
T. Anhy			,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	T.	Devonian			Т.	Ojo Alamo	
	•		***************************************		Silurian				Kirtland-Fruitland	••••••••••
			***************************************		Montoya				Farmington	
					Simpson				Pictured Cliffs Menefee	
			•••••••••••••••••••••••••••••••••••••••		Ellenburger				Point Lookout	
<b></b> .				T.	Gr. Wash	******************************		Т.	Mancos	***************************************
T. San A	ndres	522			Granite				Dakota	•••••••••••••••••••••••••••••••••••••••
					***************************************				Morrison	
	Hart	TURN'							Penn	
	•		•••••		***************************************				***************************************	
т. У			•••••	T.	***************************************			т.		*************************
TL/MIN	T. Care	359		T.		•		т.		•••••••••••••••••••••••••••••••••••••••
					FORMATIO	ON RECC	ORD		· · · · · · · · · · · · · · · · · · ·	
From	То	Thickness in Feet	Fo	rmatior	a.	From	То	Thickness in Feet	Formation	on .
0	1565	1565	Badbal							
565	2122	557	Redbol, Anh		le);					
112	<b>8912</b> 4196	790	Amby, Salt		ale					
196	4300	104	Amby, Cyp 1	Lim	•					
700 H	4416 0412	116	Amby & Line	•		ľ				
ris i	0557	345	Line Line & thel							
557 The	orte	185	Line						•	
25.	10000	91 55	Line & Shal Line		,					
1							,			
										:
		i	i			ii ii				
					a.					
					V					

### ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a	complete and correct record of the well and all work done on it so far
as can be determined from available records.	
	May 20, 1958 (Date)
Company or Operator. Signed by B. Bas. Stephensices and Company or Operator.	Address Re. Qe Box 307, Hobbie, Box Mousteo
Name D. P. DAMPF	Position or TitleDistrictFroduction Superintender