

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELL

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-offs, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	X		

Lovington, New Mexico.

July 24th, 1939.

OIL CONSERVATION COMMISSION,
Santa Fe, New Mexico.

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the
Magnolia Petroleum Co. State **NS**

Company or Operator **NE¹ NE¹** Well No. **34** in the **168** Lease
of Sec. **34E**, T. **34E**, R. **34E**, N. M. P. M.,
Vacuum Field, **Lea** County

The dates of this work were as follows: **July 17th to July 24th, 1939.**

Notice of intention to do the work was ~~(was not)~~ submitted on Form C-102 on **7/17/39** 19
and approval of the proposed plan was ~~(was not)~~ obtained. (Cross out incorrect words)

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Total depth was 5690' Put in Cement Plug 5690' to 5637', Filled with 14# Mud from 5637' to 5276' Cement plug from 5276' to 5268', filled with 14# Mud from 5268' to 5092' & Set Cement plug from 5092' to 5085' Filled with 14# Mud from 5085' to top of 7" Casing, shot 7" Casing @ 3000' & 2780' & 2485', recovered 2485' of 7" Casing 79 Jts, Set cement plug @ 1665' with 10 Sx Cement & Shot 9-5/8" Casing @ 1000' & 802' & 535', recovered 12 Jts of 9-5/8" Casing, filled with 14# Mud to with in 15' of top of surface Casing & Cemented with 15 Sx Cement to top of cellar level with 1 Jt. of 4" Pipe 4' above ground level, left 324' of 15" Surface Casing in hole.

Witnessed by **C.E. Bogwell, H.R. West,** **Magnolia Petroleum Co.,** **Drillers**
James O'Connor, Richard Dempsey, Company Title

Subscribed and sworn to before me this
24th, day of **July**, 19 **39**

Roy Yarbrough
Notary Public

5/28/42

My Commission expires

I hereby swear or affirm that the information given above is true and correct.

Name *Tony Williams*Position **Foreman**Representing **Magnolia Petroleum Co.,**Address **Box 68, Lovington, New Mexico.**

Remarks:

Roy Yarbrough
Name

OIL & GAS INSPECTOR
Title

