

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease State <input checked="" type="checkbox"/> Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. 06-341

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>	7. Unit Agreement Name
2. Name of Operator Cabot Corporation	8. Farm or Lease Name New Mexico "Q" St.
3. Address of Operator c/o Hobbs Pipe & Supply Co. P O Box 2010 Hobbs, N M	9. Well No. 1
4. Location of Well UNIT LETTER <u>L</u> , <u>1980</u> FEET FROM THE <u>South</u> LINE AND <u>560</u> FEET FROM THE <u>West</u> LINE, SECTION <u>7</u> TOWNSHIP <u>15 S</u> RANGE <u>35 E</u> NMPM.	10. Field and Pool, or Wildcat Undersigned
15. Elevation (Show whether DF, RT, GR, etc.)	12. County Lea

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data	
NOTICE OF INTENTION TO:	SUBSEQUENT REPORT OF:
PERFORM REMEDIAL WORK <input type="checkbox"/>	REMEDIAL WORK <input type="checkbox"/>
TEMPORARILY ABANDON <input type="checkbox"/>	COMMENCE DRILLING OPNS. <input type="checkbox"/>
PULL OR ALTER CASING <input type="checkbox"/>	CASING TEST AND CEMENT JOB <input type="checkbox"/>
OTHER <input type="checkbox"/>	OTHER <input type="checkbox"/>
PLUG AND ABANDON <input type="checkbox"/>	ALTERING CASING <input type="checkbox"/>
CHANGE PLANS <input type="checkbox"/>	PLUG AND ABANDONMENT <input checked="" type="checkbox"/>

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

- Set a CIBP at 10,308' w/20' cement.
- Spotted a 25 sx. cement plug at 5 1/2" casing stub at 6200'.
- Spotted a 25 sx. cement plug at Top of Glorietta at 6000'.
- Spotted a 25 sx. cement plug at 9 5/8" casing shoe at 4630'.
- Spotted a 10 sx. cement plug at surface with marker.
- Hole was loaded with mud laden fluids.

8. I hereby certify that the information above is true and complete to the best of my knowledge and belief.		
<u>Heckmiller</u>	TITLE <u>Agent</u>	DATE <u>June 3, 1970</u>
APPROVED BY <u>John W. Remyan</u>	TITLE _____	DATE _____
CONDITIONS OF APPROVAL, IF ANY:		

RECEIVED

JUN 4 1970

OIL CONSERVATION COMM.
HOBBBS, N. M.