

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS REPORTS ON WELL

Submit this report in triplicate to the Oil Conservation Commission or its proper agent within ten days after the work specified is completed. It should be signed and sworn to before a notary public for reports on beginning drilling operations, results of shooting well, results of test of casing shut-offs, result of plugging of well, and other important operations, even though the work was witnessed by an agent of the commission. Reports on minor operations need not be signed and sworn to before a notary public. See additional instructions in the Rules and Regulations of the Commission.

Indicate nature of report by checking below:

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON REPAIRING WELL	
REPORT ON RESULT OF SHOOTING OR CHEMICAL TREATMENT OF WELL		REPORT ON PULLING OR OTHERWISE ALTERING CASING	
REPORT ON RESULT OF TEST OF CASING SHUT-OFF		REPORT ON DEEPENING WELL	
REPORT ON RESULT OF PLUGGING OF WELL	X		

Hobbs, New Mexico,

October 25, 1941.

Place

Date

OIL CONSERVATION COMMISSION,  
Santa Fe, New Mexico

Gentlemen:

Following is a report on the work done and the results obtained under the heading noted above at the

J. W. Brown, Inc., State of New Mexico Well No. 1 in the  
Company or Operator  
C-101 11 of Sec. 4 T. 16 R. 25, N. M. P. M.,  
Wildcat Field, Hobbs County

The dates of this work were as follows:

Notice of intention to do the work was (was not) submitted on Form C-102 on October 7, 1941  
and approval of the proposed plan was (was not) obtained. (Cross out incorrect words.)

## DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Fridges 15 3250' and ran 5 sacks of cement and grouted it to harden for 48 hours. The 5 1/2" pipe was shot off at 4400'. The hole was then mudded back to 2950', then 10 sacks of cement run. The 5 1/2" was completely withdrawn. The hole was mudded back to 1790' and 10 sacks of cement run. The 8" pipe was shot off 275' below the surface, leaving 1425' of 8" in the hole. The hole was again mudded, to 130', and 10 sacks of cement run. The hole was then filled up and the top closed with 5 sacks of cement, which served to close the top of hole and hold a 4" registration marker in place. The marker extending 4' above ground. The slush-pit and collar leveled off.

Witnessed by

Name

Company

Title

Subscribed and sworn to before me this 27

day of October, 1941

*Norma J. Zelle*  
Notary Public

My Commission expires Nov. 20, 1942

I hereby swear or affirm that the information given above is true and correct.

Name *J. W. Brown*

Position President

Representing J. W. BROWN, INC.  
Company or Operator

Address Box 811, Roswell, New Mexico

marks:

*Ray Yarbrough*  
Name

OIL &amp; GAS INSPECTOR

Title