

NO. OF COPIES RECEIVED	
DISTRIBUTION	
SANTA FE	
FILE	
U.S.G.S.	
LAND OFFICE	
OPERATOR	

HOBBS OFFICE O. C. & C.
NEW MEXICO OIL CONSERVATION COMMISSION

DEC 9 11 38 AM '65

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input type="checkbox"/>	Fee <input checked="" type="checkbox"/>
5. State Oil & Gas Lease No.	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR.
USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. Unit Agreement Name
2. Name of Operator Sinclair Oil & Gas Company		8. Farm or Lease Name Hulda A. Townsend
3. Address of Operator P. O. Box 1920, Hobbs, New Mexico		9. Well No. 1
4. Location of Well UNIT LETTER J 1650 FEET FROM THE South LINE AND 2310 FEET FROM THE East LINE, SECTION 7 TOWNSHIP 16S RANGE 35E NMPM.		10. Field and Pool, or Wildcat Eidson Pennsylvanian
15. Elevation (Show whether DF, RT, GR, etc.) 4,047 GR		12. County Lea

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data
NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☒
CHANGE PLANS ☐
OTHER ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOB ☐
OTHER ☐
ALTERING CASING ☐
PLUG AND ABANDONMENT ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

PROPOSE TO PLUG AND ABANDON AS FOLLOWS:

Present Depth 10,715 PB. Perforated 10,664-676' and 10,684-10710'.
13-3/8" casing set at 320' and cement circulated to surface.
8-5/8" casing set at 4646' and cemented back to 1740' from surface.
5-1/2" casing set at 10,719' and cemented back to 10,085' from surface.

PROPOSE TO: Set cement plugs as follows: with hole full of heavy mud.

25 sacks cement across perfs. or CIEP set at top of perfs. w/2 sks. cement on top.
25 sacks cement in top of 5-1/2" csg stub.
25 sacks cement at 8400' top of lime.
25 sacks cement at 7300' top of Tubb.
25 sacks cement at 6180' top of Glorieta.
25 sacks cement at base of 8-5/8" casing 4646'.
25 sacks cement in top of 8-5/8" casing stub.
25 sacks cement in base of 13-3/8" casing at 320'.
10 sacks cement in top of 13-3/8" casing at surface, install regulation dry hole marker and clear and level location.

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED [Signature] TITLE Superintendent DATE 12-8-65

APPROVED BY [Signature] TITLE DATE

CONDITIONS OF APPROVAL, IF ANY:

Orig&2cc: OOC Hobbs, cc: Regional Office, cc: file