

00: VDA
JTR
F

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

1954 APR 29 AM 9:35

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE.

AREA 640 ACRES
LOCATE WELL CORRECTLY

Sinclair Oil & Gas Company

Hilda A. Townsend

(Company or Operator)

(Lease)

Well No. 1, in NW $\frac{1}{4}$ of SE $\frac{1}{4}$, of Sec. 7, T. 16 S, R. 35 E, NMPM.

Edison Pennsylvania

Pool, Los County.

Well is 1650 feet from South line and 2310 feet from East line

of Section 7-16-35 If State Land the Oil and Gas Lease No. is _____

Drilling Commenced.....1-24....., 1954..... Drilling was Completed.....3-8....., 1954.....

Name of Drilling Contractor.....**Frank Frawley Drilling Company**.....

Address..... Tulsa, Oklahoma

Elevation above sea level at Top of Tubing Head..... **4047** The information given is to be kept confidential until
....., 19.....

OIL SANDS OR ZONES

No. 1, from 10664 to 10710 No. 4, from _____ to _____

No. 2, from _____ to _____ No. 5, from _____ to _____

No. 3, from.....to..... No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from **None** to _____ feet.

No. 2, from.....to.....feet.

No. 3, from to feet.

No. 4, from to feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
13 3/8	48	N	317	Larkin			
8 5/8	32-24	N	4645	"			
5 1/2	20-17-15.5	N	10719	"		10664-10676 and 10684-10710 - Oil	
2	4.7	N	10700				

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
17 1/4	13 3/8	320	350	Halliburton		
11	8 5/8	466	2200	"		
7 7/8	5 1/2	10719	150	"		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Treated formation 10664 to 10676 and 10684 to 10710 with 1,000 gallons of mud acid.

Result of Production Stimulation.

Potentialled 518 MOD

.....10715
.....Depth Cleaned Out.....

B/ D OF DRILL-STEM AND SPECIAL TEST

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from.....feet to.....feet, and from.....feet to.....feet.
 Cable tools were used from.....feet to.....feet, and from.....feet to.....feet.

PRODUCTION

Put to Producing.....**March 18,**....., 19**54**

OIL WELL: The production during the first 24 hours was.....**518**.....barrels of liquid of which.....**100**.....% was
 was oil;% was emulsion;% water; and.....% was sediment. A.P.I.
 Gravity.....**37.5**.....

GAS WELL: The production during the first 24 hours was.....M.C.F. plus.....barrels of
 liquid Hydrocarbon. Shut in Pressure.....lbs.

Length of Time Shut in.....

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico			Northwestern New Mexico		
T. Anhy.....	1770		T. Devonian.....		T. Ojo Alamo.....
T. Salt.....	1882		T. Silurian.....		T. Kirtland-Fruitland.....
B. Salt.....	2835		T. Montoya.....		T. Farmington.....
T. Yates.....	2967		T. Simpson.....		T. Pictured Cliffs.....
T. 7 Rivers.....	3130		T. McKee.....		T. Menefee.....
T. Queen.....			T. Ellenburger.....		T. Point Lookout.....
T. Grayburg.....			T. Gr. Wash.....		T. Mancos.....
T. San Andres.....	4560		T. Granite.....		T. Dakota.....
T. Glorieta.....	6130		T.		T. Morrison.....
T. Clear fork Drinkard.....	6725		T.		T. Penn.....
T. Tubbs.....	7335		T.		T.
T. Abo.....	8105		T.		T.
T. Penn.....	10560		T.		T.
T. Wolfcamp Miss.....	9732		T.		T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	69	69	Sand & Caliche				
69	220	151	Caliche				
220	1664	1444	Redbed				
1664	1868	204	Anhydrite				
1868	2908	1040	Anhydrite & Salt				
2908	3410	502	Anhydrite & lime				
3410	4030	620	Anhydrite & Gyp				
4030	4314	284	Gyp				
4314	4608	294	Anhydrite & Gyp				
4608	5395	787	Lime				
5395	5532	137	Sandy lime				
5532	5830	298	Lime				
5830	5942	112	Sandy lime				
5942	9351	3409	Lime				
9351	9392	41	Sandy lime				
9392	10550	1158	Lime				
10550	10577	27	Lime & Shale				
10577	10587	10	Sandy lime & Shale				
10587	10657	70	Lime & Shale				
10657	10720	63	Lime				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Company or Operator.....**Sinclair Oil & Gas Company**.....
 Name.....*[Signature]*.....

4-27-54
 (Date)
 Address.....**Box 1927 Hobbs, New Mexico**.....
 Position or Title.....**Dist. Mgr.**.....