

Orig: & cc: OCO
cc: VDA
JTR
F

(Form C-103)
(Revised 7/1/52)

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Report by Checking Below

REPORT ON BEGINNING DRILLING OPERATIONS		REPORT ON RESULT OF TEST OF CASING SHUT-OFF	<input checked="" type="checkbox"/>	REPORT ON REPAIRING WELL	
REPORT ON RESULT OF PLUGGING WELL		REPORT ON RECOMPLETION OPERATION		REPORT ON (Other)	

March 19, 1954

Hobbs, New Mexico

(Date)

(Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Sinclair Oil & Gas Company

Hulda A. Townsend

(Company or Operator)

Frank Frawley Drilling Company

(Lease)

1

NW

SE

7

Well No. in the 1/4 of Sec.

(Contractor)

16 S 35 E

Edison Pennsylvanian

Lea

T. R. NPM. Pool, County.

3-12-54

The Dates of this work were as follows:

Notice of intention to do the work ~~was~~ (was not) submitted on Form C-102 on, 19, (Cross out incorrect words)

and approval of the proposed plan (was) (was not) obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

TD 10720 - Set 5 1/2" OD casing @ 10719 and cemented with 150 sacks of cement. Ran temperature survey which indicated that top of cement behind 5 1/2" OD casing @ 10085 from surface. Let set 72 hours and tested W/1000, pump pressure for 30 minutes, no decrease in pump pressure. Drilled cement plug to 10711. Perforated 5 1/2" OD casing with 4 - 1/2" Jet shots per foot from 10664 to 10676 and 10684 to 10710. Ran 10700' of 2" UE tubing, swabbed well down, acidized with 1,000 Gallons of mud acid. Maximum Pressure 2650#, Min. Press. 1300#, injection rate 1.2 Bbl. per minute. Ran swab 6 times, well started flowing. Flowed 216 Bbl. of clean oil in tank in 10 hours, thru 3/4" choke, Tub. Press. 200#.

H. W. Shaner

Sinclair Oil & Gas Company

Foreman

Witnessed by (Name) (Company) (Title)

Approved:

OIL CONSERVATION COMMISSION

I hereby certify that the information given above is true and complete to the best of my knowledge.

Name Dist. Supt.

Position Sinclair Oil & Gas Company

Representing Box 1927 Hobbs, New Mexico

Address

(Title)

(Date)