

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

Indicato	Nature	~*	Donaut	<b>L</b>	(the all the second	<b>VD</b> - 1 -
mulcate	nature	OI.	report	DV	Checking	Below

REPORT ON BEGINNING	REPORT ON RESULT OF TEST	REPORT ON
DRILLING OPERATIONS	OF CASING SHUT-OFF	REPAIRING WELL
REPORT ON RESULT	REPORT ON RECOMPLETION	REPORT ON
OF PLUGGING WELL	OPERATION	(Other)

January 4, 1954 Hobbs, N. K. (Date) (Place)

Following is a report on the work done and the results obtained under the heading noted above at the

Humble Oil & Refining Co. Hulda A. Townsend	
Company Rig No. 42 , Well No. 3 in the 1/4 MM 1/4 of Sec	9
T. 16-S, R. 35-E, NMPM., Townsend-Wolfcamp Pool, Les	.County,
The Dates of this work were as folows: 12-30-53	
Notice of intention to do the work (was not) submitted on Form C-102 on	19,

and approval of the proposed plan (was) (maximum obtained.

DETAILED ACCOUNT OF WORK DONE AND RESULTS OBTAINED

Commanded 289 joints, 10,481' of 5-1/2" casing at 10,493' with 100 sx. regular neat commant with 10% gel and 1/4# Kambreak per sk. Job complete at 3:30 A. M. 12-30-53. Top of commant at 8060'. Perforated 5-1/2" casing at 8050' with 2 - 1/2" shots. Command 2nd stage with 230 sx. 10% gel with 1# Kambreak per sk. Job completed 2:00 P. M. 12-31-53. Top of commant at

2190'. Tested casing with 1500# for 30 minutes on 1-1-54. Tested OK. No drop in pressure. Drilled plug at 8:00 P. M. 1-1-54 and tested perforations with 1500# CWP for 30 minutes. Tested OK. No drop in pressure.

Witnessed by	ble Oil & Refining Co. Tool Fusher (Company) (Title)
Approved: II CONSERVATION COMMISSION	I hereby certify that the information given above is true and complete to the best of my knowledge. Name
meb/meb	