NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

	Indicate Nature of	Report by Checking I	Below		
REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON REOF CASING SH	ESULT OF TEST UT-OFF	REPORT ON REPAIRING	WELL	
REPORT ON RESULT OF PLUGGING WELL	REPORT ON RE OPERATION	COMPLETION	REPORT ON (Other)	:	
	**********	vember 22, 1955	5 Roswe	oll, New Mexic	30
Following is a report on the work	done and the results obtain	ned under the heading	noted above at the		
Southern Petroleum Expl	eration, Inc.		Lus	ık	
(Company or Ope	erator)		(Lease)		
J. C. Crain Brillin	g Co.	, Well No3	in the	NF 1/4 of Sec	11
16s , R 35R , NMPM., To	•	Doet	Les	.	
The Dates of this work were as follows:	November 20	, 21, 22, 1955			······
		C-101	October 21		55
	/ . The Table of the second of the Tra				
nnd approval of the proposed plan (was) DETAI Hole WAS 3	(various) obtained. LED ACCOUNT OF WOR drilled to 4672. et at 4672. Cemel	8 5/8" 26 lb.	ULTS OBTAINED pipe (new) ton with	rds)	, 19 .
nnd approval of the proposed plan (was) DETAIL Hole WAR 2 1900 to to	(variety obtained. LED ACCOUNT OF WOR drilled to 4672.	8 5/8" 26 lb. ated by Halibur k nest cement.	ults obtained pipe (new) rton with Giroulated	rds)	, 19,
nand approval of the proposed plan (was) DETAIL Hole WAR 2 1900 to to	content obtained. LED ACCOUNT OF WOR drilled to 4672. et at 4672. Cemel sax 4% and 200 sa: p. 1000 lb. press	8 5/8" 26 lb. ated by Halibur k nest cement.	ults obtained pipe (new) rton with Giroulated	rds)	, 19,
nand approval of the proposed plan (was) DETAIL Hole WAR 2 1900 to to	content obtained. LED ACCOUNT OF WOR drilled to 4672. et at 4672. Cemel sax 4% and 200 sa: p. 1000 lb. press	8 5/8" 26 lb. ated by Halibur k nest cement.	ults obtained pipe (new) rton with Giroulated	rds)	, 19,
nand approval of the proposed plan (was) DETAIL Hole WAR 2 1900 to to	content obtained. LED ACCOUNT OF WOR drilled to 4672. et at 4672. Cemel sax 4% and 200 sa: p. 1000 lb. press	8 5/8" 26 lb. ated by Halibur k nest cement.	ults obtained pipe (new) rton with Giroulated	rds)	, 19,
nand approval of the proposed plan (was) DETAIL Hole WAR 2 1900 to to	content obtained. LED ACCOUNT OF WOR drilled to 4672. et at 4672. Cemel sax 4% and 200 sa: p. 1000 lb. press	8 5/8" 26 lb. ated by Halibur k nest cement.	ults obtained pipe (new) rton with Giroulated	rds)	, 19,
nand approval of the proposed plan (was) DETAIL Hole WAR 2 1900 to to	content obtained. LED ACCOUNT OF WOR drilled to 4672. et at 4672. Cemel sax 4% and 200 sa: p. 1000 lb. press	8 5/8" 26 lb. ated by Halibur k nest cement.	ults obtained pipe (new) rton with Giroulated	rds)	, 19
DETAIL Hole WAR 1 1900 to to and f	cet at 4672. Camer ax 4% and 200 sa: 0.1000 lb. pressound 0.K.	8 5/8" 26 lb. ated by Halibur k nest cement.	ults OBTAINED pipe (new) ton with Circulated De. Ho leaks		
Hole was s 1900 to to and f	cet at 4672. Camer ax 4% and 200 sa: 0.1000 lb. pressound 0.K.	8 5/8" 26 lb. ated by Haliburk neat cement. sure put on pig	ults OBTAINED pipe (new) ton with Circulated De. Ho leaks	Superintend	
DETAIL Hole Was s 1900 to to and f Witnessed by R. S. Gaston (Name)	cet at 4672. Camer ax 4% and 200 sa: 0.1000 lb. pressound 0.K.	8 5/8# 26 lb. nted by Halibur k neat cement. sure put on pir	pipe (new) rton with Circulated De. Ho leaks	Superintend	ent
DETAIL Hole Was s 1900 to to and f	cet at 4672. Cemel sax 4% and 200 sa: p. 1000 lb. pressound 0.K.	8 5/8# 26 lb. nted by Halibur k neat cement. sure put on pir	pipe (new) ton with Circulated De. Ho leaks coration, Inc.	Superintend	ent
DETAIL Hole Was s 1900 to to and f Witnessed by R. S. Gaston (Name)	cet at 4672. Cemel sax 4% and 200 sa: p. 1000 lb. pressound 0.K.	8 5/8" 26 lb. nted by Halibur k neat cement. sure put on pi; Petroleum Fx:) (Company)	pipe (new) ton with Circulated De. Ho leaks coration, Inc.	Superintend	ent
DETAIL Role Was 3 1900 to to and f Witnessed by R. S. Gaston (Name)	cet at 4672. Cemel sax 4% and 200 sa: p. 1000 lb. pressound 0.K.	Petroleum Expl (Company) I hereby certify the the best of my Name	pipe (new) ton with Circulated De. No leaks cration, Inc.	Superintend	eomplete