

Santa Fe, New Mexico

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in **QUINTUPLICATE**. If State Land submit 6 Copies

~~Stanolind Oil and Gas Company~~
(Company or Operator)

State "A"
(Lynn)

Well No. 1, in NE $\frac{1}{4}$ of NE $\frac{1}{4}$, of Sec. 12, T. 14-S, R. 35-E, NMPM.

Tongard Wolfcamp

.Pool

County.

Well is 330 feet from North line and 330 feet from West line

of Section 12 If State Land the Oil and Gas Lease No. is A-7961

Drilling Commenced 4-10-56, 19..... Drilling was Completed 7-10-56, 19.....

Name of Drilling Contractor..... **Lee Drilling Company**.....

Address.....Tulsa, Oklahoma.....

Elevation above sea level at Top of Tubing Head..... ~~3971~~..... The information given is to be kept confidential until ~~not confidential~~....., 19.....

No. 1, from 10652 to 10717 No. 4, from _____ to _____

No. 2, from.....to..... No. 5, from.....to.....

No. 3, from.....to..... No. 6, from.....to.....

REFERENCES AND FURTHER READING

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.

No. 2, from to feet.

No. 3, from.....to.....feet.

No. 4, from.....to.....feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
13-3/8"	14	New	349	Homes			Surface
8-5/8"	24	New	1722	Homes			Intermediate
5-1/2"	15.5 & 17	New	10720	Homes		10652-10668 10681-10717 10681-10707	Oil String

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. BAGS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
17-1/2"	13-3/8	360	440	Hotchkiss Plug		
11	8-5/8	4700	1615 8% gal 100 sack	Hotchkiss Plug		
7-7/8"	5-1/2	10720	45 sack 4% gal	Hotchkiss Plug		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Perforated 10.652-10.666 10.684-10.717 with 5 shots per foot, washed 8,000 gallons

155 REG. 0014

Result of Production Stimulation..... See Reverse Side

Depth Cleaned Out...

RECORD OF DRILL-STEM AND SPECIAL TS

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

TOOLS USED

Rotary tools were used from 0 feet to 10720 feet, and from feet to feet.
Cable tools were used from feet to feet, and from feet to feet.

PRODUCTION

Put to Producing 7-18, 19 56

OIL WELL: The production during the first 24 hours was 216 barrels of liquid of which 100 % was
was oil; % was emulsion; % water; and % was sediment. A.P.I.
Gravity 40°

GAS WELL: The production during the first 24 hours was M.C.F. plus barrels of
liquid Hydrocarbon. Shut in Pressure lbs.

Length of Time Shut in

PLEASE INDICATE BELOW FORMATION TOPS (IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE):

Southeastern New Mexico				Northwestern New Mexico			
T. Anhy.	1890			T. Devonian			T. Ojo Alamo
T. Salt				T. Silurian			T. Kirtland-Fruitland
B. Salt				T. Montoya			T. Farmington
T. Yates	2385			T. Simpson			T. Pictured Cliffs
T. 7 Rivers				T. McKee			T. Menefee
T. Queen	3945			T. Ellenburger			T. Point Lookout
T. Grayburg				T. Gr. Wash.			T. Mancos
T. San Andres	4622			T. Granite			T. Dakota
T. Glorieta	6298			T. Wolfcamp	9630		T. Morrison
T. Drinkard	7455			T.			T. Penn.
T. Tubbs				T.			T.
T. Abo				T.			T.
T. Penn.				T.			T.
T. Miss.				T.			T.

FORMATION RECORD

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0	878	878	Red bed				
878	1888	1010	Redbed & Anhy.				
1888	2800	912	Anhy. & Salt				
2800	3403	603	Anhy. & Gyp				
3403	4638	1235	Anhy. & Lime				
4638	9864	5226	Lime				
9864	9920	56	Lime & Chert				
9920	10156	236	Lime				
10156	10179	23	Lime & Chert				
10179	10262	83	Lime				
10262	10375	113	Lime & Shale				
10375	10720	345	Lime				

ATTACH SEPARATE SHEET IF ADDITIONAL SPACE IS NEEDED

I hereby swear or affirm that the information given herewith is a complete and correct record of the well and all work done on it so far as can be determined from available records.

Company or Operator Stanolind Oil and Gas Company Address Box 68 Hobbs, New Mexico (Date)
Name [Signature] Position or Title Field Superintendent