

## NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

## MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION  
SANTA FE, NEW MEXICOHobbs, New Mexico  
(Place)April 30, 1957  
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

**Sinclair Oil & Gas Company** **L. M. Blackman** Well No. **1** in **Unit**  
(Company or Operator) Lease  
**SE** 1/4 **SE** 1/4 of Sec. **15**, T. **14S**, R. **39E**, NMPM., **Undesignated** Pool  
(40-acre Subdivision)  
**Lea** County.

FULL DETAILS OF PROPOSED PLAN OF WORK  
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

TD 12962 -

Set 7"OD Casing @ 12806' - Top cement behind 7"OD Casing @ 8815' from surface

Perf. 7"OD Casing f/ 12740-750

do 12644-682

do 12626-650 each set Perf. squeezed off w/ 100 Sks. cement

Flugged back Depth 11035-

Perf. 7"OD Casing f/ 11008 - 11024 - spontaneous combustion Tested dry after several acid treatments

Propose to cover Perforations w/ 25 Sks. Cement-

Knock off 7"OD Casing @ 8800' and set a 25 Sack cement plug in top of 7"OD Casing

9 5/8"OD Casing set @ 4732' w/ 3700 Sks. - Cement Circulated to Surface

Propose to set 25 Sks. cement plug in bottom of 9 5/8"OD Casing - Keeping hole full heavy mud-

Set 25 Sack cement plug in bottom of 13 5/8"OD Surface Casing Approx. 305'

Set 4"x "Regulation Marker" in Top of 9 5/8"OD Casing &amp; bottom of collar in 15 Sacks cement extending 4' above surface level

Approved....., 19.....  
Except as follows: **MAY 1 1957****Sinclair Oil & Gas Company**  
Company or Operator

By.....

Position..... **Dist. Supt.**  
Send Communications regarding well to:Approved  
OIL CONSERVATION COMMISSIONBy..... **E. P. Wicker**Name..... **C. C. Salter**

Title.....

Address..... **520 E. Br. Way, Hobbs, N.M.**

