

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

HOBBS OFFICE OCC

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work is begun. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICOLovington, New Mexico
(Place)January 25, 1960
(Date)

Gentlemen:

Lovington, New Mexico

Following is a Notice of Intention to do certain work as described below at the

Amerada Petroleum Corporation State S.T. "A" Well No. **1** in **B** (Unit)
(Company or Operator)
C- NW/4 NW 17 T 16-S R 35-E NMPM, Edison Pennsylvania Pool
(40-acre subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

10,750' Total Depth 10,749' BDD 5-1/2" Casing set @ 10,750' With Casing perforations from 10,739' to 10,749', 5-1/2" Casing cemented W/350 Sx. top Cement outside 5-1/2" Casing @ 9109'. 8-5/8" Casing set @ 4674' and cemented with 2000 Sx. Cement, top cement outside 8-5/8" Casing @ 541'. 13-3/8" casing set @ 340' with 300 Sx. Cement, Cement Circulated. Top Anhydrite @ 1806'. Top Salt 1910', Top San Andres 4655', Base San Andres 6250'. Plan to Cut off 5-1/2" Casing at Approximately 9089' and 8-5/8" Casing @ Approx. 541' and recover above cut off casing. Set 25 Sx. Cement Plug in 5-1/2" Casing from 10,000'-10,208'. 30 Sx. Cement Plug in and out top of cut off 5-1/2" Casing @ 9089'. 30 Sx. Cement Plug in Base San Andres @ 6250'. 30 Sx. Cement Plug in Top of San Andres in and out 8-5/8" Casing, Cag. set @ 4674'. 30 Sx. Cement Plug in and out top of cut off 8-5/8" Casing @ 541'. 30 Sx. Cement Plug in and out bottom of 13-3/8" Casing set @ 340'. 10 Sx. Cement Plug in top of 13-3/8" OD Casing W/4" x 4' Dry Hole Marker in top 13-3/8" OD Cag. Offset Operators has been Notified.

Approved....., 19.....
Except as follows: JAN 25 1960

Amerada Petroleum Corporation
Company or Operator
By *[Signature]*
Assistant District Superintendent
Position.....
Send Communications regarding well to:

Approved
OIL CONSERVATION COMMISSION

Amerada Petroleum Corporation
Name.....
Box 636 - Lovington, New Mexico
Address.....

Title.....

