

Submit 3 Copies  
to Appropriate  
District Office

State of New Mexico  
Energy, Minerals and Natural Resources Department

Form C-103  
Revised 1-1-89

DISTRICT I  
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II  
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III  
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION  
P.O. Box 2088  
Santa Fe, New Mexico 87504-2088

WELL API NO.

30-025-02805

5. Indicate Type of Lease

STATE ☐

FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A  
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"  
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL  
WELL ☒

GAS  
WELL ☐

OTHER

2. Name of Operator

Hondo Oil & Gas Company

3. Address of Operator

P. O. Box 2208, Roswell, NM 88202

7. Lease Name or Unit Agreement Name

Eidson Ranch

8. Well No.

1

9. Pool name or Wildcat

Townsend ABO

4. Well Location

Unit Letter E : 1980 Feet From The North Line and 990 Feet From The West Line

Section

26

Township

16S

Range 35E

NMPM

Lea

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

3966' GR

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☒

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

13 3/8" csg @ 328' (TOC @ Surface), 9 5/8" csg @ 4920' (TOC est'd @ surface)  
5 1/2" Liner @ 4572'-12,780', CIBP @ 8007', ABO perfs @ 8724'-8786'.

PLUGGING PROCEDURE APPROVED BY PAUL KAUTZ ON 10/22/90.

(1). Set retainer @  $\pm$  5350' & squeeze cmt bad csg @ 5488'-6353' w/ 200 sx  
leaving 50' of cmt on top of retainer.

(2). Spot 100' cmt plug over 5 1/2" Liner top from 4625'-4525'.

(3). Spot 100' cmt plug @ top of salt from 2350'-2250'.

(CONTINUED) *on back*

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

*E. L. Buttross Jr.*

TITLE

Petroleum Engineer

DATE 10/22/90

TYPE OR PRINT NAME

E. L. Buttross, Jr.

TELEPHONE NO. (505) 625-6732

(This space for State Use)

APPROVED BY JERRY SEXTON  
DISTRICT SUPERVISOR

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

XC: B. Stubbs, J. Handley, File

- (4) . If cmt top behind 9 5/8" csg is below 13 3/8" csg, perf 4 holes @ 375' & circ cmt to surface.
- (5) . Spot 10 sx surface plug.
- (6) . Install dry hole marker.