

WELLS WITHIN THE AREA OF REVIEW

WELL	Type	Construction size	depth	sx cmt	Date Drilled	Location	Depth	Completion
Humble Oil & Refining Co. #1 M.W. Graham	☛	11 3/4"	309'	300	10-26-55	Sec.9,T-15-S,R-36-E	13,600'	3-6-56
		8 5/8"	4,900'	2100		660' FSL & 1980' FWL	13,511'	PBTD.
		5 1/2"	13,600'	1970				
Sunray Mid-Continent Oil Co. #1 J.D. Graham	☛	13 3/8"	377'	400	11-12-55	Sec.9,T-15-S,R-36-E	13,631'	2-24-56
		8 5/8"	4,749'	2300		330' FSL & 2310' FEL	13,622'	PBTD.
		5 1/2"	13,631.	450				
Magnolia Petroleum Co. #1 J.D. Black (re-enter by Magnolia)	☛	13 3/8"	460'	450	6-10-51	Sec.9,T-15-S,R-36-E	13,763'	12-13-51
		9 5/8"	4,750'	3200	3-12-52	1980' FNL & 1980' FWL	-----	PBTD
		7"	11,503'	1183				7-18-52
G.E. Hall #1 M. Graham	☛	13 3/8"	312'	400	2-25-56	Sec.9,T-15-S,R-36-E	13,547'	6-22-56
		8 5/8"	4,750	300		330' FSL & 990' FWL	-----	PBTD
V-F Petroleum, Inc. #1 Graham	●	12 3/4"	401'	475	9-13-81	Sec.9,T-15-S,R-36-E	13,635'	1-13-82
		8 5/8"	4,706'	1650		2310' FSL & 430' FWL	-----	PBTD
		5 1/2"	13,544'	1850				
Moran Exploration, Inc. #2 Gann	●	13 3/8"	405'	425	5-22-80	Sec.9,T-15-S,R-36-E	13,657'	12-10-80
		8 5/8"	4,712'	1600		2310' FNL & 990' FWL	-----	PBTD
		5 1/2"	13,454'	1950				
Shell Oil Company #1 State "GB"	☛	13 3/8"	354'	350	6-3-55	Sec.16,T-15-S,R-36-E	13,672'	9-1-55
		8 5/8"	4,748'	2200		660' FNL & 1980' FWL	-----	PBTD
		5 1/2"	13,672'	200				
Shell Oil Company #6 State "GA"	☛	13 3/8"	352'	400	8-6-55	Sec.16,T-15-S,R-36-E	13,682'	11-9-55
		8 5/8"	4,749'	1700		660' FNL & 990' FWL	13,639'	PBTD
		5 1/2"	13,682'	200				
Shell Oil Company #7 State "GA"	☛	13 3/8"	353	400	11-9-55	Sec.16,T-15-S,R-36-E	13,630'	2-1-56
		8 5/8"	4,749'	1650		660' FNL & 2310' FEL	13,586'	PBTD
		5 1/2"	13,629'	250				