

			6134-6164 pin point porosity, yellow fluorescence by samples.
Drill Stem Test	6124	6164	San Andres, 2 packers, 1 hr. 5/8" BHC and 1" SC, No WC, Rec. 270' drlg. mud, no shows, oil, gas or water, BHFP 55-110#, 15 min. S-I BHP 1645#, HH 2770-2770#.
Lime	6164	7480	1-1/4° @ 6230, 1-1/4° @ 6335, 1-3/4° @ 6420, 1-3/4° @ 6385, 1-3/4° @ 6570, 2° @ 6660, 1-1/2° @ 6760, 1-1/2° @ 6885, 1° @ 6980, 1-1/2° @ 7060, 1-1/2° @ 7138, 1° @ 7205, 1-1/4° @ 7340, 1-1/2° @ 7410, 1° @ 7475, <u>Top of Glorietta @ 6230</u>
Lime and sand	7480	7523	
Lime	7523	8231	1-3/4° @ 7650, 1° @ 7980, 1-1/2° @ 7935 1-1/2° @ 8005, 1° @ 8071, 1° @ 8170, <u>Top of Abo @ 8120</u>
Sandy lime	8231	8282	
Lime and shale	8282	9132	1° @ 8375, 1/2° @ 8465, 1/2° @ 8580, 1/2° @ 8700, 1° @ 8800, 1° @ 8932, 1° @ 9130. <u>DFC 8803 = 8809</u>
Lime	9132	9166	
Lime and shale	9166	9211	
Lime	9211	9244	1° @ 9212 Basal Abo 9214-9244 trace to 20% pin point and inter-crystalline porosity with bright yellow fluorescence by samples.
Attempted Drill Stem Test	9214	9244	Basal Abo, leaky drill pipe.
Drill Stem Test	9214	9244	Basal Abo, 2 packers, 1 hr. 5/8" BHC and 1" SC, No WC, Rec. 5' drlg. mud, no shows, oil, gas or water, BHFP zero, 15 min. S-I BHP zero, HH 4500-4500#.
Lime	9244	9425	1/2° @ 9350, 1° @ 9420
Lime and shale	9425	9450	
Lime	9450	9481	
Lime and shale	9481	9500	1° @ 9500
Lime	9500	9560	
Lime and dolomite	9560	9587	1° @ 9600, 1° @ 9660, 1° @ 9762
Lime	9587	9762	<u>Top of Permo Penn @ 9690</u> 9744-9762 finely crystalline tan lime, trace inter-crystalline porosity, trace blue fluorescence, by samples.
Drill Stem Test	9720	9762	Permo Penn, 2 packers, 45 min. 5/8" BHC and 1" SC, No WC, Rec. 10' drlg. mud, no shows, oil, gas or water, BHFP 20#, 15 min. S-I BHP 2650#, HH 4970-4920#.
Lime	9762	9880	
Lime and chert	9880	10006	1/2° @ 9960
Lime	10006	10031	
Lime and chert	10031	10048	3/4° @ 10048
Lime, chert and black shale	10048	10067	
Lime, chert and shale	10067	10086	

