NO. OF COPIES RECEIVED		
DISTRIBUTION		Form C-103 Supersedes Old
SANTA FE		C-102 and C-103
FILE	NEW MEXICO OIL CONSERVATION COMMISSION	Effective 1-1-65
U.S.G.S.	-	
	-	5a. Indicate Type of Lease
OPERATOR	_	State Fee X
		5. State Oil & Gas Lease No.
SUNF		- hummmmm
(DO NOT USE THIS FORM FOR P USE "APPLIC.	DRY NOTICES AND REPORTS ON WELLS PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. ATION FOR PERMIT	
··	Stand Property for Sach Proposels.)	7. Unit Agreement Name
WELL WELL	OTHER-	
2. Name of Operator		8. Farm or Lease Name
3. Address of Operator		J. D. GRAHAM
		9. Well No.
P. 0. BOX 1861, N 4. Location of Well	1IDLAND, TEXAS 79701	1
0	2210 Fact 200	10. Field and Pool, or Wildcat
UNIT LETTERU,	2310 FEET FROM THE East LINE AND 330 FEET F	ROM CAUDILL PERMO PENN
THE South	TION 9 TOWNSHIP 15-S RANGE 36-E	
LINE, SEC	TION TOWNSHIP RANGE NE	лем. <u>() </u>
	15. Elevation (Show whether DF, RT, GR, etc.)	12, County
$\Delta m m m m m m m m m m m m m m m m m m m$		
Check	Appropriate Box To Indicate Nature of Notice, Report or	Other Data
NOTICE OF		ENT REPORT OF:
PERFORM REMEDIAL WORK	PLUG AND ABANDON REMEDIAL WORK	ALTERING CASING
TEMPORARILY ABANDON	COMMENCE DRILLING OPNS.	PLUG AND ABANDONMENT
	CHANGE PLANS CASING TEST AND CEMENT JOB	
OTHER	OTHER	
12. 2		
<i>work)</i> SEE RULE 1103.	Operations (Clearly state all pertinent details, and give pertinent dates, includ	ding estimated date of starting any proposed
3-28-75: MIRU DA&S.	Parted rods while pulling and attempt to fish	
3-31-75: Loaded hol	e w/10# brine. Pulled rods and tbg. out of we	11 and layed down.
4-3-75: Ran Baker	Mod. "N" CIBP on tbg. & set @ 10,150'. Loaded	hole w/220 bbls. 9.5#
mud and sp	otted 15 sx. cmt. plug 10,150-10,000'.	
5-15-75: Shot 5-1/2	" csg. @ 8603' and pulled total of 258 joints.	
	. cmt. plug from 8620-8468'.	
	. cmt. plug from 6124-5946' and 60 sx. cmt. pl	10 from 1740 45401
	· and programmer or and on sx. alle. pl	uy Trom 4/49-4543'.

5-21-75: Shot 8-5/8" csg. @ 504' and pull and lay down. Spot 125 sx. cmt. from 543-300' and spot 20 sx. cmt. plug from 60' to surface. Weld on cap and install marker. Well is P&A and ready for inspection.

RECEIVED

JUN 4 1975

OL CONSERVATION COMM. Hobbs. N. M.