

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

HOBBS OFFICE OCC

MISCELLANEOUS NOTICES

Submit this notice in **TRIPPLICATE** to the District Office, Oil Conservation Commission, before the work is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL		NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE	X	NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE	X	NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Roswell, New Mexico

(Place)

September 22, 1959

(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Shell Oil Company State GA Well No. 6 in D
(Company or Operator) Lessee (Unit)
NW 1/4 NW 1/4 of Sec. 16, T-15-S, R-36-E, NMPM., Caudill-Davonian Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

PROPOSED OPERATION:

1. Pull production string.
2. Perforate 13,548' - 13,558', & 13,592' - 13,606' w/2-1/2" JSPP.
3. Run tubing with retrievable bridge plug and hookwall packer. Straddle test new intervals individually. If oil bearing treat each interval w/500 gallons 15% MCA.
4. Swab test.
5. Reset retrievable BP to test for water shut off above 13,440' & above 13,395'.
(Other settings may be designated depending on results of these tests)
6. If water shut off is obtainable with a packer, treat above packer w/2000 gallons 15% acid. Swab test. If results satisfactory, pull tubing, packer and retrievable BP.
7. If newly perforated zones produce water, set CIBP at appropriate depth for water shut off capped with 2 sacks cement.
8. If new zones produce oil, leave all zones open.
9. Run production string and place on production.

Approved..... SEP 24 1959
Except as follows:....., 19.....Approved
OIL CONSERVATION COMMISSIONBy.....
Title..... Engineer District 1

Shell Oil Company

Company or Operator

Original Signed By

By..... R. A. Lowery R. A. LOWERY

Position..... District Exploitation Engineer

Send Communications regarding well to:

Name..... Shell Oil Company

Address..... Box 845, Roswell, New Mexico