

NO. OF COPIES RECEIVED		
DISTRIBUTION		
NTA FE		
LE		
S.G.S.		
AND OFFICE		
PERATOR		

NEW MEXICO OIL CONSERVATION COMMISSION

Form C-103
Supersedes Old
C-102 and C-103
Effective 1-1-65

5a. Indicate Type of Lease	
State <input checked="" type="checkbox"/>	Fee <input type="checkbox"/>
5. State Oil & Gas Lease No. B-2341	
7. Unit Agreement Name	
8. Farm or Lease Name Lea HQ State	
9. Well No. 1	
10. Field and Pool, or Wildcat Dean Permo Penn	
12. County Lea	

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT -" (FORM C-101) FOR SUCH PROPOSALS.)

OIL WELL ☒ GAS WELL ☐ OTHER- ☐

1. Name of Operator

Gulf Oil Corporation

3. Address of Operator

Box 670, Hobbs, New Mexico 88240

4. Location of Well

UNIT LETTER M, 660 FEET FROM THE South LINE AND 660 FEET FROM THE West LINE, SECTION 25 TOWNSHIP 15-S RANGE 36-E NMPM.

15. Elevation (Show whether DF, RT, GR, etc.)

3788' GL

16.

Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

SUBSEQUENT REPORT OF:

PERFORM REMEDIAL WORK ☐
TEMPORARILY ABANDON ☐
PULL OR ALTER CASING ☐
OTHER ☐

PLUG AND ABANDON ☒
CHANGE PLANS ☐
OTHER ☐

REMEDIAL WORK ☐
COMMENCE DRILLING OPNS. ☐
CASING TEST AND CEMENT JOBS ☐
OTHER ☐

ALTERING CASING ☐
PLUG AND ABANDONMENT ☐
OTHER ☐

17. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

11,653' TD.

Pull producing equipment. Load hole with abandonment mud. Spot 90 sack Class C cement plug on top of packer at 11,475' to approximately 10,600', across perforations 10,740' to 10,768'. Run free point and cut and recover 5-1/2" casing from approximately 7450'. Spot 80 sack Class C cement, 100', plug across 5-1/2" casing stub. Spot 50 sack Class C cement plug from 6400' to 6200', across top of Glorietta. Spot 50 sack Class C cement plug from 5000' to 4800', across 8-5/8" shoe at 4934'. Spot 30 sack Class C cement plug from 2100' to 2200', across top of salt. Spot 15 sack Class C cement plug 50' to surface. Install dry hole marker and clean location.

24 hr. notice

18. I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNED H. J. Buzeale

TITLE Area Engineer

DATE March 29, 1973

APPROVED BY Joe D. Ramsey
Dist. T. Supv.

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY