NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Oct 17 3 29 PM '63

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

Notice of Intention to Change Plans	Notice of Intention to	NOTICE OF INTENTION
	TEMPORARILY ABANDON WELL	TO DRILL DEEPER
Notice of Intention to Plug Well	X NOTICE OF INTENTION TO PLUG BACK	Notice of Intention to Set Liner
Notice of Intention to Squeeze	Notice of Intention to Acidize	Notice of Intention to Shoot (Nitro)
Notice of Intention to Gun Perforate	Notice of Intention (Other)	Notice of Intention (Other)
OIL CONSERVATION COMMI Santa Fe, New Mexico	SSION Hobbs, New Mexic	October 16, 1963
Gentlemen:	(1 1400)	
Following is a Notice of Inter	ntion to do certain work as described below at the.	
Soceny Mobil Oil Comp	or Operator)	
	of Operator)	(Unit) MPM.,Sean Porme Penn. Pool
Tee	County.	,
(FULL DETAILS OF PROPOSED PLA FOLLOW INSTRUCTIONS IN THE RULES A	
(Top of com Porfs: 10,654-10,682 Propose to run free p Cire. hole v/mmd lade	<pre>v/425 sx., 9 5/8" @ 4934' w/2400 wat en 7" @ 3160') ?' Squmesed eint indicator. Cut & pull 7" c a fluid. Spet 25 sx cement plug 434', and 10 sx cement plug at s</pre>	sx., 7" @ 11,642' w/1900 sx. asing at approximately 3000'. in stub of 7" casing. Spot
PB: 10,685' Gag: 13 3/8" @ 434' (Top of com Porfs: 10,654-10,682 Propose to rum free p Gire, hole w/mmd lade 25 sx coment plug at menument. All offset operators	ent en 7" @ 3160') ?' Squmesed eint indicator. Cut & pull 7" c en fluid. Spet 25 ax cement plug	sx., 7" © 11,642' w/1900 sx. asing at approximately 3000'. in stub of 7" casing. Spot wrface. Install regulation
PB: 10,685' Gag: 13 3/8" @ 434' (Top of com Porfs: 10,654-10,682 Propose to run free p Gire, hole v/mud lade 25 sx cement plug at menument.	ent en 7" @ 3160') ?' Squmesed peint indicator. Cut & pull 7" c on fluid. Spet 25 ex cement plug 434', and 10 ex cement plug at s have been metified by cepy of th	sx., 7" @ 11,642' w/1900 sx. asing at approximately 3000'. in stub of 7" casing. Spot wrface. Install regulation is C-102.
PB: 10,685' Gag: 13 3/8" @ 434' (Top of com Porfs: 10,654-10,682 Propose to run free p Gire. hole v/mad lade 25 ax coment plug at menument. All offset operators	ment en 7" @ 3160') ?' Squmesed peint indicator. Cut & pull 7" c on fluid. Spet 25 ax cement plug 434', and 10 ax cement plug at s have been metified by cepy of th	<pre>sx., 7" @ 11,642' w/1900 sx. asing at approximately 3000'. in stub of 7" casing. Spot wrface. Install regulation is C-102. Mobil 011 Company, Inc.</pre>
PB: 10,685' Gag: 13 3/8" @ 434' (Top of com Porfs: 10,654-10,682 Propose to run free p Gire. hole w/mad lade 25 sx coment plug at menument. All effset operators	ment en 7" @ 3160') ?' Squmesed peint indicator. Cut & pull 7" c on fluid. Spet 25 ax cement plug 434', and 10 ax cement plug at s have been metified by cepy of th	sx., 7" @ 11,642' w/1900 sx. asing at approximately 3000'. in stub of 7" casing. Spot wrface. Install regulation is C-102.
PB: 10,685' Gag: 13 3/8" @ 434' (Top of com Porfs: 10,654-10,682 Propose to run free p Gire. hole v/mmd lade 25 sx coment plug at menument. All effset operators Approved	ent en 7" @ 3160') ?' Squmesed peint indicator. Cut & pull 7" c on fluid. Spet 25 ax cement plug 434', and 10 ax cement plug at s have been metified by cepy of th 	<pre>sx., 7* @ 11,642' w/1900 sx. asing at approximately 3000'. is stub of 7* casing. Spot wrfase. Install regulation is C-102. Mobil Oil Company, Inc.</pre>
PB: 10,685' Gag: 13 3/8" @ 434' (Top of com Porfs: 10,654-10,682 Propose to run free p Gire. hole v/mad lade 25 sx coment plug at menument. All offset operators	ent en 7" @ 3160') ?' Squmesed peint indicator. Cut & pull 7" c on fluid. Spet 25 sx cement plug 434', and 10 sx cement plug at s have been metified by cepy of th 	<pre>sx., 7" @ 11,642' w/1900 sx. asing at approximately 3000'. is stub of 7" casing. Spot wrfase. Install regulation is C-102. Mobil Oil Company, Inc. Company or Operate McManue</pre>

Address..

Title.

.....

Box 1800, Hobbs, New Maxico

A set of the set o

ان المحمد الم المحمد المحمد

 $\phi^{(1)} \rightarrow \phi^{(2)} \phi^{(1)} \phi^{(2)} \phi^$

📲 S 👡 S S S La March (1986)

• and a second of the second second