## NEW MEXICO OIL CONSERVATION COMMISSION

್ಷ ನ ಪ್ರಾ

25

Santa Fe, New Mexico

## MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

## Indicate Nature of Notice by Checking Below

Notice of LATENTION NOTICE OF LAURAL NOTICE OF		TEMPORARILY ABANDON WELL	NOTICE OF INTENTION TO DRILL DEEPER	
TO SQUEERS  TO ACTORYS  NOTICE OF INTENTION TO SHOOT (NIRD)  NOTICE OF INTENTION TO SHOOT (NIRD)    NOTICE OF INTENTION OF GUN PERFORMENT  NOTICE OF INTENTION (OTHERS)  NOTICE OF INTENTION (OTHERS)  NOTICE OF INTENTION (OTHERS)    DIL CONSERVATION COMMISSION ANTA FE, NEW MEXICO  Image: Compary of OPERATY 12, 1961 (Casto)  Image: Compary of OPERATY 12, 1961 (Casto)    Gendemen:  Following is a Notice of Intention to do certain work as described below at the.  THE CHIQ. OIL COMPANY 15 (Compary of OPERATY)  Image: Company of OPERATY 12, 1961 (Casto)    Minimum  Of Sec. 35 (Casto)  T. 153 (Casto)  R. 268 (NMPM, Deam Permo Pann (Casto)  D (Casto)    Minimum  Void Sec. 35 (Casto)  T. 153 (Casto)  R. 268 (NMPM, Deam Permo Pann (Casto)  D (Casto)    Minimum  Void Sec. 35 (Casto)  T. 153 (Casto)  R. 268 (NMPM, Deam Permo Pann (Casto)  D (Casto)    Minimum  Void Sec. 35 (Casto)  T. 153 (Casto)  R. 268 (NMPM, Deam Permo Pann (Casto)  D (Casto)    Minimum  Void Sec. 35 (Casto)  T. 153 (Casto)  R. 268 (NMPM, Deam Permo Pann (Casto)  D (Casto)    Set company return to the stand pall caston  Sec. 35 (Casto)  Sec. 397-10,4081  THE CHIO OIL COMPANY (Caston)    Spot 200' comeant plug 4034-5034.  Spot 501 (Si cemea				
OGUN PRAFORATE  (OTHER)  NOTICE OF INTENTION    DIL CONSERVATION COMMISSION ANNTA FE, NEW MEXICO  Sammary 12, 1961    DIL CONSERVATION COMMISSION ANNTA FE, NEW MEXICO  Sammary 12, 1961    Generation  (Others)  Sammary 12, 1961    Sendemen:  Following is a Notice of Intention to do certain work as described below at the.  THE CHIO OIL COMPARY'S    Chio-Sinelair A. C. Dean *A" That  Well No. 1  D    (Company of Operator)  Leve  Well No. 1  D    (Company of Operator)  Leve  Well No. 1  D    (Company of Operator)  Leve  Well No. 1  D    (Concord)  In D  Control  Control    (Concord)  Kord  NMPM. Dean Permo Permo  D    (Concord)  FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)  11,295'.  Plan to plug & abandon well, as follows:  THE CHIO 0,397-10,408' with 100 see leaving approx. 100' cement on top of revising.    Spot 200' cement plug at peint of out-off, lapping plug 100' above and below point of Spot 200' cement plug (\$1,453,4'-503,1'.  Spot 200' cement well marker and fill cellar.    Fill spaces between plugs with mod laden fluid.  Company of operator    pproved  .19				
ANTA FE, NEW MEXICO				
Sentemen: Following is a Notice of Intention to do certain work as described below at the		Nobbs, New M	iexico Jamery	12. 1961
Following is a Notice of Intention to do certain work as described below at the	- 1	(Place)	(Data)	·····
Chie-Sinclair A. C. Dean "A" Thait				
M  M  M  Model				
Lea				
Lea	(40-acre Subdivision) /4 of Sec. 3	T. 158 , R. 36E , NI	MPM. Dean Permo Penn	
FULL DETAILS OF PROPOSED PLAN OF WORK (FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)    11,295'. Plan to plug & abandon well, as follows:    Set comment retainer at 10,350', and exampt 7" casing perfs 10,397-10,408' with 100 sates and paper of retainer.    Gut 7" casing at free point and pall easing.    Spot 200' cement plug at point of out-off, lapping plug 100' above and below point of 5pot 200' cement plug 4834'-5034'.    Spot 50' cement plug 50'-0'.    Install permanent well marker and fill cellar.    Fill spaces between plugs with mud ladem fluid.    pproved				
pproved Company or Operator By	11,295'. Plan to plug . Set cement retainer at	4 abandon well, as follows: 10.350', and cement 7" easing	7000	th 100 sax,
pproved Position Asst. Supt.	11,295'. Plan to plug Set cement retainer at leaving approx. 100' ca Cut 7" casing at free p Spot 200' cement plug a Spot 200' cement plug b Spot 50' cement plug 50 Install permanent well ;	& abandon well, as follows: 10,350', and coment 7" casing ment on top of retainer. oint and pull easing. t point of out-off, lapping p 834'-5034'. '-0'. marker and fill cellar.	perfs 10,397-10,408' wit	
pproved Position.	11,295'. Plan to plug Set cement retainer at leaving approx. 100' ca Cut 7" casing at free p Spot 200' cement plug a Spot 200' cement plug b Spot 50' cement plug 50 Install permanent well ;	& abandon well, as follows: 10,350', and coment 7" casing ment on top of retainer. oint and pull easing. t point of out-off, lapping p 834'-5034'. '-0'. marker and fill cellar.	perfs 10,397-10,408' wit	
Approved By	11,295'. Plan to plug Set cement retainer at leaving approx. 100' ca Cut 7" casing at free p Spot 200' cement plug a Spot 200' cement plug b Spot 50' cement plug 50 Install permanent well ;	& abandon well, as follows: 10,350', and coment 7" casing ment on top of retainer. oint and pull easing. t point of out-off, lapping p 834'-5034'. '-0'. marker and fill cellar.	perfs 10,397-10,408' wit	
Approved Position Asst. Supt.	11,295'. Plan to plug Set cement retainer at leaving approx. 100' cm Cut 7" casing at free p Spot 200' cement plug a Spot 200' cement plug 4 Spot 50' cement plug 50 Install permanent well 1 Fill spaces between plug	& abandon well, as follows: 10,350', and commont 7" casing ment on top of retainer. oint and pull easing. t point of out-off, lapping pi 834'-5034'. '-0'. marker and fill cellar. gs with mud laden fluid.	perfs 10,397-10,408' with lug 100' above and below	
Approved	11,295'. Plan to plug Set cement retainer at leaving approx. 100' cm Cut 7" casing at free p Spot 200' cement plug a Spot 200' cement plug 4 Spot 50' cement plug 50 Install permanent well 1 Fill spaces between plug	& abandon well, as follows: 10,350', and coment 7" casing ment on top of retainer. oint and pull easing. t point of out-off, lapping p 834'-5034'. '-0'. marker and fill cellar. gs with mud laden fluid.	perfs 10,397-10,408' with lug 100' above and below ME OHIO OIL COMPANY	
	11,295'. Plan to plug Set cement retainer at leaving approx. 100' cm Cut 7" casing at free p Spot 200' cement plug a Spot 200' cement plug 4 Spot 50' cement plug 50 Install permanent well 1 Fill spaces between plug	& abandon well, as follows: 10,350', and coment 7" casing ment on top of retainer. oint and pull easing. t point of out-off, lapping p 834'-5034'. '-0'. marker and fill cellar. gs with mud laden fluid.	perfs 10,397-10,408' with lug 100' above and below ME OHIO OIL COMPANY	
Name THE OHIO OIL COMPANY	11,295'. Plan to plug Set cement retainer at leaving approx. 100' ca Cut 7" casing at free p Spot 200' cement plug a Spot 200' cement plug a Spot 50' cement plug 50 Install permanent well n Fill spaces between plug proved	& abandon well, as follows: 10,350', and comment 7" casing ment on top of retainer. oint and pull easing. t point of out-off, lapping pind 834'-5034'. '-0'. marker and fill cellar. gs with mud laden fluid. By	perfs 10,397-10,408' with lug 100' above and below THE CHIO OIL COMPANY Company or Operator Asst. Supt.	point of cut

Address ....

Box 2107, Hobbs, New Mexico

Title..

.

. .

~ •

· · · · ·

DISTRIBUTION: MODC Wr. J. A. Grims Mr. L. H. Shearer Mr. D. V. Ritley Mr. T. A. Steale Mr. T. A. Steale Mr. T. C. Webb Mr. R. H. Pasther

.