Orig: & ee: OGC oe: FHR JTR

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

NOBES OFFICE OCC

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

	Indicate Nature of Report by Chec	THIS DOLOW		
PORT ON BEGINNING LILLING OPERATIONS	REPORT ON RESULT OF TES OF CASING SHUT-OFF		ON NG WELL	
PORT ON RESULT PLUGGING WELL	REPORT ON RECOMPLETION OPERATION	REPORT (Other)	ON	
	146+44+1/ Na	meh 1, 1955	Hobbs, New H	exic
Following is a report on the work	(Date)		(Place)	
Sinclair Oil & Gas Comp	done and the results obtained under the h			
(Company or Ope	······································	J. P. Den	***************************************	
A. W. Thompson Inc. (Contractor)	, Well No.	in the SR	¹ / ₄	35
	Wildest Po			
Dates of this work were as follows:	2-24-55			
confintentian to do the work (11)				
se of intention to do the work (was)	(was not) submitted on Form C-102 on	(Cross out incorrec	et words)	, 19
approval of the proposed plan (was)	(was not) obtained.			
ided 0 1:AN 2-24-55	ED ACCOUNT OF WORK DONE AND			
dded @ 1:AN 2-24-55 323 - set 13 3/8" OD estated to surface. set 48 hours and tested	ED ACCOUNT OF WORK DONE AND sing 0 322 and comented with scaling with 500% pump preserves in pressure. Resum	h 375 sacks of	sement, Cement	
dded @ l:AK 2-24-55 323 - set 13 3/8" OD estated to surface. set 48 hours and tested Lling easent plug. No d	sing 6 322 and comented with sasing with 500% pump presidences in pressure. Resum	h 375 sacks of sure for 30 mim od drilling.	resear	
ided 6 liAK 2-24-55 323 - set 13 3/8" OD entated to surface. set 48 hours and tested thing easent plug. No dested the surface.	sing © 322 and cemented wit casing with 500# pump pres cerease in pressure. Resum	h 375 sacks of sure for 30 mim od drilling.	sement, Cement	
dded @ 1:AK 2-24-55 323 - set 13 3/8" OD estated to surface. set 48 hours and tested Lling easent plug. No descent plug. No descent plug. No descent plug.	saing @ 322 and comented with scaling with 500% pump presidences in pressure. Resum Sinclair Oil & (Company)	h 375 sacks of sure for 30 mim od drilling.	resear	afte
added @ liAN 2-24-55 323 - set 13 3/8" OD enlated to surface. set 48 hours and tested lling easent plug. No delay. (Name)	Sinclair Oil (Company) I hereby ce to the best Name	th 375 sacks of sacks	Ferenan (Title)	afte
dded 8 1:AN 2-24-55 323 - set 13 3/8" OD estated to surface. set 48 hours and tested lling easent plug. No description of the conservation of th	saing © 322 and comented with score pump presidencese in pressure. Result (Company) I hereby ce to the best Name	h 375 sacks of sacks	Ferenan (Title)	afte

> i de la companya de la co

general en de de la companya della companya de la companya della c