

DUPLICATE

NEW MEXICO OIL CONSERVATION COMMISSION
Santa Fe, New Mexico

(Form O-102)
(Revised 7/1/52)
RECEIVED
JAN 13 1954
OIL CONSERVATION COMMISSION

MISCELLANEOUS NOTICES

Submit this notice in TRIPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	<input checked="" type="checkbox"/>	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO

Hobbs, New Mexico
(Place)

January 12, 1954
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Shell Oil Company Montieth Well No. 1 in "np"
(Company or Operator) (Unit)
SE 1/4 SE 1/4 of Sec. 14, T. 16-S, R. 36-E, NMPM, Undesignated Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

VERBAL APPROVAL RECEIVED PER TELEPHONE CONVERSATION BETWEEN MR. D. F. JAHMS OF SHELL OIL COMPANY AND MR. S.J. STANLEY OF OIL CONSERVATION COMMISSION TO PLUG AND ABANDON MONTIETH NO. 1. WE PROPOSE TO PLUG AND ABANDON AS FOLLOWING:

- (1) Lead hole with mud
- (2) Pull tubing with hookwall packer and hydraulic hold down
- (3) Run tubing open ended to 10,200' and spot 20 sack neat cement plug - calculated fill 10,035' - 10,200'. (Note: Perforations in the Wolfcamp were 10,135' - 10,155')
- (4) Stretch test casing. Shoot off and pull all recoverable 5-1/2" casing.
- (5) Run tubing open ended to 3240' and spot 20 sack cement plug - calculated fill 3178' - 3240'
- (6) Pull tubing to 30' and spot 10 sack cement plug at surface and erect 4" x 4' marker and clean location.

Approved JAN 27 1954, 19.....
Except as follows:

Approved
OIL CONSERVATION COMMISSION
By S. J. Stanley
Title Engineer District 1

Shell Oil Company
Company or Operator
By F. D. Leigh Original signed by F. D. Leigh

Position Division Mechanical Engineer
Send Communications regarding well to:

Name Shell Oil Company
Address Box 1957, Hobbs, New Mexico