

AREA 640 ACRES
LOCATE WELL CORRECTLY

Santa Fe, New Mexico

DUPLICATE

WELL RECORD

Mail to District Office, Oil Conservation Commission, to which Form C-101 was sent not later than twenty days after completion of well. Follow instructions in Rules and Regulations of the Commission. Submit in QUINTUPLICATE.

(Company or Operator)

(Lease)

Well No. 2, in SE 1/4 of SE 1/4, of Sec. 25, T. 16S, R. 36E, NMPM.

Lovington Paddock

Pool, Lee

County.

Well is 130 feet from South line and 130 feet from East line.

of Section 25 If State Land the Oil and Gas Lease No. is 1

Drilling Commenced Aug. 1, 1959 Drilling was Completed Sept. 2, 1959

Name of Drilling Contractor.....**Mohin Drilling Company**.....

Address Hobbs, New Mexico

Elevation above sea level at Top of Tubing Head 3041' 27" The information given is to be kept confidential until

Not confidential 19

OIL SANDS OR ZONES

No. 1, from 6083' to 6260' No. 4, from.....to.....

No. 2, from.....to..... No. 5, from.....to.....

No. 3, from.....to..... No. 6, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.

No. 2, from.....to.....feet.

No. 3, from to feet.

No. 4, from.....to.....feet.

CASING RECORD

SIZE	WEIGHT PER FOOT	NEW OR USED	AMOUNT	KIND OF SHOE	CUT AND PULLED FROM	PERFORATIONS	PURPOSE
2-5/8"	124	New	2048'	Float			Surface
3-1/2"	174	New	6048'	"			Production

MUDDING AND CEMENTING RECORD

SIZE OF HOLE	SIZE OF CASING	WHERE SET	NO. SACKS OF CEMENT	METHOD USED	MUD GRAVITY	AMOUNT OF MUD USED
11"	8-5/8"	2104'	800	Halliburton		
7-7/8"	5-1/2"	6083'	225	"		

RECORD OF PRODUCTION AND STIMULATION

(Record the Process used, No. of Qts. or Gals. used, interval treated or shot.)

Acidized open hole section 6083-6249' with 7500 Gals. acid.

Result of Production Stimulation. After acid treatment well flowed 208.39 Bbls. oil in 19½ hours through open 2" tubing. No test taken prior to acid treatment.

..Depth Cleaned Out.

If drill-stem or other special tests or deviation surveys were made, submit report on separate sheet and attach hereto

Rotary tools were used from 0 feet to 6260 feet, and from _____ feet to _____ feet.

Cable tools were used from _____ feet to _____ feet, and from _____ feet to _____ feet.

Length of Time Shut in.....

Northwestern New Mexico		
T. Anhy.....	2002'	T. Devonian.....
T. Salt.....	2100'	T. Silurian.....
B. Salt.....	2900'	T. Montoya.....
T. Yates.....	3105'	T. Simpson.....
T. 7 Rivers.....		T. McKee.....
T. Queen.....		T. Ellenburger.....
T. Grayburg.....		T. Gr. Wash.....
T. San Andres.....	4665'	T. Granite.....
T. Glorieta.....	6025'	T.
T. Drinkard.....		T.
T. Tubbs.....		T.
T. Abo.....		T.
T. Penn.....		T.
T. Miss.....		T.
		T. Ojo Alamo.....
		T. Kirtland-Fruitland.....
		T. Farmington.....
		T. Pictured Cliffs.....
		T. Menefee.....
		T. Point Lookout.....
		T. Mancos.....
		T. Dakota.....
		T. Morrison.....
		T. Penn.....
		T.
		T.
		T.
		T.

From	To	Thickness in Feet	Formation	From	To	Thickness in Feet	Formation
0'	2082'	2082'	Red bed, sand & caliche				
2082	2180	98	Anhydrite				
2180	2900	800	Anhydrite & salt				
2900	4010	1090	Anhydrite & lime				
4010	6260	2250	Lime				

Sept. 9, 1953 (Date)

Company or Operator Skelly Oil Company

Name R. L. Sullivan

Address Box 38 - Hobbs, New Mexico

Position or Title Dist. Supt.