

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

MISCELLANEOUS NOTICES

Submit this notice in TRIPPLICATE to the District Office, Oil Conservation Commission, before the work specified is to begin. A copy will be returned to the sender on which will be given the approval, with any modifications considered advisable, or the rejection by the Commission or agent, of the plan submitted. The plan as approved should be followed, and work should not begin until approval is obtained. See additional instructions in the Rules and Regulations of the Commission.

Indicate Nature of Notice by Checking Below

NOTICE OF INTENTION TO CHANGE PLANS		NOTICE OF INTENTION TO TEMPORARILY ABANDON WELL		NOTICE OF INTENTION TO DRILL DEEPER	
NOTICE OF INTENTION TO PLUG WELL	X	NOTICE OF INTENTION TO PLUG BACK		NOTICE OF INTENTION TO SET LINER	
NOTICE OF INTENTION TO SQUEEZE		NOTICE OF INTENTION TO ACIDIZE		NOTICE OF INTENTION TO SHOOT (Nitro)	
NOTICE OF INTENTION TO GUN PERFORATE		NOTICE OF INTENTION (OTHER)		NOTICE OF INTENTION (OTHER)	

OIL CONSERVATION COMMISSION
SANTA FE, NEW MEXICO619 West Texas Avenue, Midland, Texas
(Place)March 27, 1961
(Date)

Gentlemen:

Following is a Notice of Intention to do certain work as described below at the.....

Union Oil Company of California George Spires Well No. 1-30 in D
(Company or Operator) (Unit)
KW 1/4 NW 1/4 of Sec. 30, T. 16-S, R. 36-E, NMPM., Wildcat Pool
(40-acre Subdivision)
Lea County.

FULL DETAILS OF PROPOSED PLAN OF WORK
(FOLLOW INSTRUCTIONS IN THE RULES AND REGULATIONS)

It is proposed to plug and abandon subject well in the following manner:

- Set 100' cement plug in open hole from 13,072' to total depth of 13,172'.
- Set 200' cement plug in open hole from 11,200' to 11,400'.
- Set 25 ex. cement plug above top of Wolfcamp at approximately 9500'.
- Set 25 ex. cement plug above top of Glorietta at approximately 6200'.
- Set 100' cement plug in and out of 9-5/8" casing shoe at 4153'.
- Set 100' cement plug on top of any recoverable 9-5/8" casing estimated at 700'.
- Set 100' cement plug in and out of bottom of 13-3/8" casing at 369'.
- Set 10 ex. cement plug in top of 13-3/8" surface casing.
- Identify location with a 4" O.D. pipe marker.

Verbal permission to plug and abandon this well in the above manner was received from Mr. E. F. Engorewist, Hobbs, New Mexico, on March 24, 1961.

Approved....., 19.....
Except as follows:

Union Oil Company of California
Company or Operator
By.....

Position..... Production Clerk
Send Communications regarding well to:

Approved
OIL CONSERVATION COMMISSION

By.....
Title.....

Name..... Union Oil Company of California
Address..... 619 West Texas Avenue, Midland, Texas

