MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 days after the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

instructions in the Rules and I		e Nature of Report by Checking Be	elow		
REPORT ON BEGINNING DRILLING OPERATIONS	RE	PORT ON RESULT OF TEST CASING SHUT-OFF	REPORT ON REPAIRING WELL	,	
REPORT ON RESULT OF PLUGGING WELL		PORT ON RECOMPLETION ERATION	REPORT ON (Other)		
		February 16, 1954	Hobbs, Hew Mexico		
Following is a report on	the work done and th	e results obtained under the heading	noted above at the		
(Com	pany or Operator)	State AC (Lease)			
Les County Cesing	Pullers (Contractor)	, Well No1	in the NE	····· ,	
			Cou		
			cy 14, 1954 Inclusive		
Notice of intention to do the	work (was) (was/you) s	ubmitted on Form C-102 on	(Cross out incorrect words)	,	
and approval of the proposed					
	DETAILED ACCOU	UNT OF WORK DONE AND RES	ULTS OBTAINED		
	DETAILED ACCOU	UNT OF WORK DONE AND RES			
Plugging was compl	DETAILED ACCOU	UNT OF WORK DONE AND RES	ULTS OBTAINED		
Plugging was compl DEPTHS 13480 - 13400	DETAILED ACCOUNTS. OF CEMENT 50 sx.	y 14, 1954 with cement	ULTS OBTAINED	erval	
Plugging was compl <u>DEPTHS</u> 13480 - 13400 12460 - 12310	eted on Februar SX. OF CEMENT 50 sx. 100 sx.	INT OF WORK DONE AND RESULT OF WORK DONE AND RESULT OF WORK DONE AND RESULT OF THE PROPERTY OF	ults obtained plugs set at the following inte	erval	
Plugging was compl DEPTHS 13480 - 13400 12460 - 12310 12150 - Bridge Plu	eted on Februar SX. OF CEMENT 50 sx. 100 sx. ag # 80 sx.	INT OF WORK DONE AND REST TY 14, 1954 with cement p All intervals filled Pulled casing as for Approx. 6400'	ults obtained plugs set at the following intended with heavily mud laden fluid. llows: - 52" casing	erval	
Plugging was complete by the property of the p	eted on Februar SX. OF CEMENT 50 sx. 100 sx. ag # 80 sx.	INT OF WORK DONE AND REST TY 14, 1954 with cement p All intervals filled Pulled casing as for Approx. 6400'	ults obtained plugs set at the following inte	erval	
Plugging was completed by the property of the	oted on Februar SX. OF CEMENT 50 sx. 100 sx. 10 sx. 10 cement 25 sx. 25 sx.	Pulled casing as for Approx. 6400' Approx. 1500'	plugs set at the following into plugs set at the following into distribution with heavily mud laden fluid llows: - 52" casing - 9-5/8" casing	er va l	
Plugging was compl DEPTHS 13480 - 13400 12460 - 12310 12150 - Bridge Plu 11830 - Bridge Plu 10600 - 10400 8100 - 8064 6400 - 6335	DETAILED ACCOUNTS. SX. OF CEMENT 50 sx. 100 sx.	Pulled casing as for Approx. 6400' A 4" pipe marker was	plugs set at the following into the plugs set at the following into the with heavily mud laden fluid. 1 llows: - 5½ casing - 9-5/8 casing s set to extend 4 above ground	erval	
Plugging was completed by the property of the	SX. OF CEMENT 50 sx. 100 sx. 100 sx. 10 cement 25 sx. 25 sx. 25 sx.	INT OF WORK DONE AND RESULT OF WORK DONE AND RESULT OF WILL OF MILE OF THE PUBLISHED OF THE PUBLISHED OF THE WILL OF THE WILL DONE AND PROX. 1500° Approx. 1	plugs set at the following interest with heavily mud laden fluid llows: - 52" casing - 9-5/8" casing set to extend 4' above ground and ground surface restored to	erwal	
Plugging was compl DEPTHS 13480 - 13400 12460 - 12310 12150 - Bridge Plu 11830 - Bridge Plu 10600 - 10400 8100 - 8064 6400 - 6335	DETAILED ACCOUNTS. SX. OF CEMENT 50 sx. 100 sx.	All intervals filled Pulled casing as for Approx. 6400' Approx. 1500' A 4" pipe marker was Pits will be filled form with surrounding	plugs set at the following into the plugs set at the following into the with heavily mud laden fluid. 1 llows: - 5½ casing - 9-5/8 casing s set to extend 4 above ground	erwal	
Plugging was complete. 13480 - 13400 12460 - 12310 12150 - Bridge Plut 11830 - Bridge Plut 10600 - 10400 8100 - 8064 6400 - 6335 3200 - 3135 1500 - 1474	DETAILED ACCOUNTS. SX. OF CEMENT 50 sx. 100 sx. 100 sx. 10 cement 25 sx. 25 sx. 25 sx. 25 sx. 20 sx. 10 sx.	All intervals filled Pulled casing as for Approx. 6400' Approx. 1500' A 4" pipe marker was Pits will be filled form with surrounding will be filed when the surrounding will be	plugs set at the following interplugs set at the following interplugs with heavily mud laden fluid. llows: - 5½" casing - 9-5/8" casing set to extend 4' above ground and ground surface restored to ag terrain. A supplemental rep	erval	
Plugging was completed by the second by the	DETAILED ACCOUNTS. SX. OF CEMENT 50 sx. 100 sx. 100 sx. 10 cement 25 sx. 25 sx. 25 sx. 20 sx. 10 sx.	All intervals filled Pulled casing as for Approx. 6400' Approx. 1500' A 4" pipe marker was Pits will be filled form with surrounding will be filled when the Stanolind Oil and Gas (Company)	plugs set at the following interest with heavily mud laden fluid. llows: - 5½" casing - 9-5/8" casing s set to extend 4' above ground and ground surface restored to ag terrain. A supplemental repthis work is completed. Company	d levo cor	
Plugging was completed by the provided by the provided by the plugging was completed by the plug	DETAILED ACCOUNTS. SX. OF CEMENT 50 sx. 100 sx. 100 sx. 10 cement 25 sx. 25 sx. 25 sx. 20 sx. 10 sx. 10 sx.	All intervals filled Pulled casing as for Approx. 6400' Approx. 1500' A 4" pipe marker was Pits will be filled form with surrounding will be filled when the Stanolind Oil and Gas (Company)	plugs set at the following interest with heavily mud laden fluid. llows: - 5½" casing - 9-5/8" casing s set to extend 4' above ground and ground surface restored to ag terrain. A supplemental repthis work is completed. Company	d levo cor	
Plugging was completed by the second by the	DETAILED ACCOUNTS. SX. OF CEMENT 50 sx. 100 sx. 100 sx. 10 cement 25 sx. 25 sx. 25 sx. 20 sx. 10 sx. 10 sx.	All intervals filled Pulled casing as for Approx. 6400' Approx. 1500' A 4" pipe marker was Pits will be filled form with surrounding will be filled when to the best of my Name Alfa.	plugs set at the following interest of with heavily mud laden fluid. Illows: - 5½" casing - 9-5/8" casing set to extend 4' above ground and ground surface restored to a supplemental repthis work is completed. Company	d levo cor	
Plugging was completed by the second by the	DETAILED ACCOUNTS SX. OF CEMENT 50 sx. 100 sx. 100 sx. 100 sx. 100 sx. 25 sx. 25 sx. 25 sx. 20 sx. 10 sx. 10 sx.	All intervals filled Pulled casing as for Approx. 6400' Approx. 1500' A 4" pipe marker was Pits will be filled form with surrounding will be filled when to the best of my Position	plugs set at the following interest with heavily mid laden fluid. Illows: - 5½" casing - 9-5/8" casing set to extend 4' above ground and ground surface restored to ag terrain. A supplemental repthis work is completed. Company	d levo cor	

	A		
			·
			:
			•
•			:
	·	,	· · · · · · · · · · · · · · · · · · ·
			i .