NEW MEXICO OIL CONSERVATION COMMISSION Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

instructions in the Rules and Regulation	ant operations, even though the work is of the Commission. Indicate Nature of Report by			E	
	II.				
REPORT ON BEGINNING DRILLING OPERATIONS	REPORT ON RESULT OF OF CASING SHUT-OFF	TEST	REPORT ON REPAIRING WELL		
REPORT ON RESULT OF PLUGGING WELL	REPORT ON RECOMPLET OPERATION	TION	REPORT ON (Other)		
	April 13, 1	953	Hobbs, New	Mexico	
Following is a report on the work	done and the results obtained under	tne heading not	ed above at the		
Following is a report on the work done and the results obtained under the Stanolind Oil and Gas Company			State AC		
(Company or Op	erator) , Well I		(25000)	of Sec. 31	
(Contractor	• •				
г. 16-8 , R. 36-В , NМРМ.,					
The Dates of this work were as folows:	April 11-13, 1953			•••••	
Notice of intention to do the work () (was not) submitted on Form C-102	on	ross out incorrect words)	, 19	
		•		•	
and approval of the proposed plan) (was not) obtained.				
DETAI	ILED ACCOUNT OF WORK DONE			of nov 12.	
On April 13, 1953 3/8" casing landed at 4 cement. Circulated to	at 12:30 A. H. 30 hours 1991 and comented with 37	ad elapsed sacks mix	i since running 483° ted 8% gel plus 100 :	sacks neat	
On April 13, 1953 3/8" casing landed at 4 cement. Circulated to	at 12:30 A. M. 30 hours 1991 and cemented with 375 surface. as tested with 450 psi for no appreciable drop in pro-	ad elapsed sacks mix	i since running 483° ted 8% gel plus 100 :	sacks neat	
On April 13, 1953 3/8" casing landed at 4 cement. Circulated to Casing shut off wa plug. Since there was	at 12:30 A. M. 30 hours 1991 and cemented with 375 surface. as tested with 450 psi for no appreciable drop in pro-	ad elapsed sacks mix	i since running 483° ted 8% gel plus 100 :	sacks neat	
On April 13, 1953 3/8" casing landed at 4 cement. Circulated to Casing shut off wa plug. Since there was	at 12:30 A. M. 30 hours 1991 and cemented with 375 surface. as tested with 450 psi for no appreciable drop in pro-	ad elapsed sacks mix	i since running 483° ted 8% gel plus 100 :	sacks neat	
On April 13, 1953 3/8" casing landed at 4 cement. Circulated to Casing shut off wa plug. Since there was	at 12:30 A. M. 30 hours 1991 and cemented with 375 surface. as tested with 450 psi for no appreciable drop in pro-	ad elapsed sacks mix	i since running 483° ted 8% gel plus 100 :	sacks neat	
On April 13, 1953 3/8" casing landed at 4 cement. Circulated to Casing shut off wa plug. Since there was Well was spudded 4	at 12:30 A. M. 30 hours 1991 and cemented with 375 surface. as tested with 450 psi for no appreciable drop in pro-	ad elapsed sacks mix 30 minute essure, dr	i since running 483° ked 8% gel plus 100° ses before and after rilling operations w	sacks neat	
On April 13, 1953 3/8" casing landed at 4 cement. Circulated to Casing shut off wa plug. Since there was Well was spudded 4 Witnessed by A. C. Blackburn (Name)	at 12:30 A. M. 30 hours lays and cemented with 37: surface. as tested with 450 psi for no appreciable drop in psi psi psi psi for no appreciable drop in psi	and Gas C	ted 8% gel plus 100 ses before and after rilling operations were the information given above is	sacks neat drilling ere resumed	
On April 13, 1953 3/8" casing landed at 4 cement. Circulated to Casing shut off wa plug. Since there was Well was spudded 4 Witnessed by A. C. Blackburn (Name)	at 12:30 A. M. 30 hours lays and comented with 375 surface. Is tested with 450 psi for no appreciable drop in pro-10-53. Stanolind Cil (Company) COMMISSION I he to the content of the	and Gas Compy	ted 8% gel plus 100 ses before and after rilling operations were the information given above is	sacks neat drilling ere resumed	

Address P. O. Box 68 - Hobbs, New Mexico

	· · · · · · · · · · · · · · · · · · ·	
i.		
	1 1 1 1	! :
		:
	i I	: !
	i I 1	
	!	
	· ·	
	1	:
	-	
	: : i	
		į
	ı	