

NEW MEXICO OIL CONSERVATION COMMISSION

Santa Fe, New Mexico

Notice of Intention to Drill

Notice must be given to the Oil Conservation Commission or its proper agent and approval obtained before drilling begins. If changes in the proposed plan are considered advisable, a copy of this notice showing such changes will be returned to the sender. Submit this notice in triplicate. One copy will be returned following approval. See additional instructions in Rules and Regulations of the Commission.

Hobbs, New Mexico

September 19, 1941

OIL CONSERVATION COMMISSION
Santa Fe, New Mexico.
Gentlemen:

You are hereby notified that it is our intention to commence the drilling of a well to be known as

SKELLY OIL COMPANY

State "S"

Well No. 1 in CSE SE

Company or Operator Lease
of Sec. 35, T. 16S, R. 36E, N. M. P. M., S. Lovington Field, Lea County

N.

The well is 660 feet (N.) ~~xx~~ of the South line and 660 feet ~~xx~~ (W.) of the East line of Section 35.

(Give location from section or other legal subdivision lines. Cross out wrong directions.)

If state land the oil and gas lease is No. Unknown, Assignment No.

If patented land the owner is

Address

If government land the permittee is

Address

The lessee is Skelly Oil Company

Address Tulsa, Oklahoma

AREA 640 ACRES
LOCATE WELL CORRECTLY

We propose to drill well with drilling equipment as follows: Rotary tools,
top to total depth. Contractor - Lee Drilling Co., Tulsa, Oklahoma.

The status of a bond for this well in conformance with Rule 39 of the General Rules and Regulations of the Commission is as follows:

We propose to use the following strings of casing and to land or cement them as indicated:

Size of Hole	Size of Casing	Weight Per Foot	New or Second Hand	Depth	Landed or Cemented	Sacks Cement
15"	13"	40#	S.H.	80'	Cemented	15 - dumped.
9 1/4"	7-5/8"	18#	New	2100'	Cemented	425- Halliburton
6 1/2"	5-1/2"	17#	New	4500'	Cemented	200- Halliburton

If changes in the above plan become advisable we will notify you before cementing or landing casing. We estimate that the first productive oil or gas sand should occur at a depth of about 4600 feet.

Additional information: The 13" casing will be conductor pipe. In cementing the 7-5/8" OD casing cement shall be circulated back to bottom of cellar. Sufficient time shall be allowed for cement to thoroughly set before drilling plugs on both strings.

Approved _____, 19____
except as follows: SEP 24 1941

Sincerely yours,

SKELLY OIL COMPANY

Company of Operator

By

Position

District Supte

Send communication regarding well to

Name

Skelly Oil Co.

Address

Hobbs, New Mexico.

OIL CONSERVATION COMMISSION,

By

Title

Oil & Gas Inspector