

Submit 3 Copies
to Appropriate
District Office

State of New Mexico
Energy, Minerals and Natural Resources Department

Form C-103
Revised 1-1-89

DISTRICT I
P.O. Box 1980, Hobbs, NM 88240

DISTRICT II
P.O. Drawer DD, Artesia, NM 88210

DISTRICT III
1000 Rio Brazos Rd., Aztec, NM 87410

OIL CONSERVATION DIVISION
P.O. Box 2088
Santa Fe, New Mexico 87504-2088

WELL API NO.

5. Indicate Type of Lease

STATE ☒

FEE ☐

6. State Oil & Gas Lease No.

E-7766

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT"
(FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

OIL
WELL ☒

GAS
WELL ☐

OTHER

2. Name of Operator

Penroc Oil Corporation

3. Address of Operator

P.O. Box 5970, Hobbs, NM 88241

8. Well No.

1

9. Pool name or Wildcat

Lovington Abo

4. Well Location

Unit Letter M : 330 Feet From The SOUTH Line and 990 Feet From The WEST Line

Section

36

Township

16 S

Range

36 E

NMPM

LEA

County

10. Elevation (Show whether DF, RKB, RT, GR, etc.)

11.

Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐

PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐

CHANGE PLANS ☐

PULL OR ALTER CASING ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☒

ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐

PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: Comply w/ R-9431 ☐

12. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103.

7.13.91 thru 7.16.91

Follow-up report to work done on the captioned well as per approval dated February 15, 1991:

Reel workover unit July 13, 1991. Pulled sub pump. Bar bond log and determined TOC @ 5850' Perf 2 holes @ 5760'. Set RBP @ 9045' w/ 25xx. sd on top. Set Howco ret. @ 5678'. Couldnt pump into perms. acid w/ 200 gal. Pump 75 xxx. @ 2BPM & 3200'. Perf 2 holes @ 4360'. Pumped into perm @ 2BPM & 800'. Pumped 375 xxx. w/ ret. set @ 4293'. Did not add cement. TOC by temp. log: 3730'. LD rental tubing. Well shut-in for future evaluation, either to plug as is or return to production.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Graham J. Merchant

TITLE

President

DATE

7/19/91

TYPE OR PRINT NAME

M. J. (Merch) Merchant

TELEPHONE NO.

(505) 397-3596

(This space for State Use)

ORIGINAL SIGNED BY JERRY SEXTON

DISTRICT I SUPERVISOR

APPROVED BY

TITLE

DATE

CONDITIONS OF APPROVAL, IF ANY:

CASE NO. 10154
Order No. R-9431

(2) Prior to initiating injection within one-half mile of any of the wells shown on Exhibit "B", the applicant shall perform remedial cement operations on said wells in a manner which will assure that these wellbores will not serve as a conduit for migration of injected fluid to the satisfaction of the supervisor of the Habbbs district office of the Division.

EXHIBIT "B"
CASE NO. 10154
ORDER NO. R-9431

<i>Operator</i>	<i>Lease</i>	<i>Well No.</i>	<i>Location</i>	<i>Sec-Twp-Rge</i>
Greenhill Petroleum Corp.	Lovington Paddock Ut.	7	330' FSL - 330' FEL	25-16-36
Greenhill Petroleum Corp.	Lovington Paddock Ut.	13	880' FNL - 330' FWL	36-16-36
Greenhill Petroleum Corp.	Lovington Paddock Ut.	29	2130' FSL - 2130' FWL	36-16-36
Greenhill Petroleum Corp.	Lovington Paddock Ut.	41	810' FSL - 2130' FWL	36-16-36
Greenhill Petroleum Corp.	Lovington Paddock Ut.	57	1980' FNL - 695' FEL	06-17-37
Texaco Producing Inc.	State P	3	800' FSL - 330' FWL	32-16-37
Amerada Hess	State L "A"	8	560' FNL - 660' FEL	01-17-36
Amerada Hess	State L "A"	9	660' FNL - 1880' FEL	01-17-36
Amerada Hess	State L "A"	10	1650' FNL - 660' FEL	01-17-36
Amerada Hess	State L "A"	11	1650' FNL - 1980' FEL	01-17-36
Amerada Hess	State L "A"	12	2310' FSL - 2310' FWL	01-17-36
Penroc	State "E" TR 18	17	1650' FNL - 2310' FWL	01-17-36
Penroc	State "E" TR 18	19	1650' FNL - 990' FWL	01-17-36
Penroc	State AE	1	330' FSL - 990' FWL	36-16-36

*Complied with
Dec 2, 1937
Order 9-14-41*