NEW MEXICO OIL CONSERVATION COM MISSION Santa Fe, New Mexico

MISCELLANEOUS REPORTS ON WELLS

Submit this report in TRIPLICATE to the District Office, Oil Conservation Commission, within 10 dates the work specified is completed. It should be signed and filed as a report on Beginning Drilling Operations, Results of test of casing shut-off, result of plugging of well, result of well repair, and other important operations, even though the work was witnessed by an agent of the Commission. See additional instructions in the Rules and Regulations of the Commission.

structions in the Rules and Regulation	Indicate Nature of Report	by Checking Bel)W	
PORT ON BEGINING RILLING OPERATIONS	REPORT ON RESULT OF CASING SHUT-OFF	OF TEST X	REPORT ON REPAIRING WELL	· .
EPORT ON RESULT	REPORT ON RECOMPOSE OPERATION	LETION	REPORT ON (Other)	
	Vovember	r 26, 1952	Hobbs, No	ew Mexico
	(Date)	. 20, 2//2		(Place)
		lar and booding n	oted above at the	
	done and the results obtained und		State "AL"	
Cities Production C	orporation			
(Company or of Warren-Bradshaw Exp (Contractor) (Contractor) (Contractor) (Contractor) (Contractor) (Contractor) (Contractor)	loration Co. W	2 /ell No	NW SN in the ¹ /4	¹ / ₄ of Sec,
(Contracto	or) Lovington-Abo		Lea	County
16-S 30-3, NMPM.,	10.11.6.01	Pool,		Gounty.
he Dates of this worl were as folows:.	Nowember 14 and 7	21a 17.7~		
otice of intention to do the work (wa	••••	(no	t required)	10
erice of intention to do the work (wa	s) (was not) submitted on Form C-	-102 on	(Cross out incorrect words)	, 19
DETA	d to a total depth of 3	3320' in lim	e. Ran 95 1/10 j	oints 8 5/8" ks with 4%
This well was drilled OD 32 and 24 casing gel, 110 tacks strate November 1.9, 1952.	d to a total depth of 3, 3305.08 set at 3319.2 a crete and 400 sacks not coment was allowed to some with all valves cl	3320' in lim 28 and cement.	e. Ran 95 1/10 j ted with 1764 sac Plug was down a casing shut-ff	t 12:25 P.M. was tested
This well was drilled OD 32 and 24 casing gel, 110 tacks strate November 1.9, 1952.	d to a total depth of 3, 3305.08 set at 3319.2 a crete and 400 sacks n	3320' in lim 28 and cement.	e. Ran 95 1/10 j ted with 1764 sac Plug was down a casing shut-ff	t 12:25 P.M. was tested
This well was drilled OD 32 and 24 casing gel, 110 tacks strate November 1.9, 1952.	d to a total depth of 3, 3305.08 set at 3319.2 a crete and 400 sacks no coment was allowed to sure with all valves clilling was resumed.	3320 in lim 28 and cement. set 48 hours Losed during	e. Ran 95 1/10 j ted with 1764 sac Plug was down a , casing shut-ff ; a 30 minute peri	t 12:25 P.M. was tested od with no
This well was drilled OD 32 and 24 casing gel, 110 tacks strate November 1.9, 1952. With 1000 pound president in pressure. D	d to a total depth of 3, 3305.08 set at 3319.2 a crete and 400 sacks not coment was allowed to sure with all valves cliving was resumed. Cities Productives	3320 in lim 28 and cement. set 48 hours Losed during	e. Ran 95 1/10 j ted with 1764 sac Plug was down a casing shut-off a 30 minute peri	t 12:25 P.M. was tested
This well was drilled OD 32 and 24 casing gel, 110 tacks strate November 19, 1952. With 1000 pound president in pressure. D	d to a total depth of 3, 3305.08 set at 3319.2 a crete and 400 sacks not coment was allowed to some with all valves clarilling was resumed. Cities Productions	3320 in lim 28 and cement. Bet 48 hours Losed during	e. Ran 95 1/10 j ted with 1764 sac Plug was down a casing shut-ff a 30 minute peri	t 12:25 P.M. was tested od with no
This well was drilled OD 32 and 24 casing gel, 110 sacks strate November 1.9, 1952. With 1000 pound president in pressure. D	d to a total depth of 3, 3305.08 set at 3319.2 a crete and 400 sacks not coment was allowed to some with all valves clarilling was resumed. Cities Products	3320 in lim 28 and cement. Bet 48 hours Losed during	e. Ran 95 1/10 j ted with 1764 sac Plug was down a casing shut-off a 30 minute peri	t 12:25 P.M. was tested od with no
This well was drilled OD 32 and 24 casing gel, 110 tacks strate November 1.9, 1952. With 1000 pound president in pressure. D	d to a total depth of 3, 3305.08 set at 3319.2 a crete and 400 sacks not coment was allowed to some with all valves clarilling was resumed. Cities Products	3320 in lim 28 and cement Beat cement. Bet 48 hours Losed during Company) Liberaly certify to	e. Ran 95 1/10 j ted with 1764 sac Flug was down a , casing shut-off , a 30 minute peri	t 12:25 P.M. was tested od with no
This well was drilled OD 32 and 24 casing gel, 110 tacks strate November 19, 1952. With 1000 pound president in pressure. Description of the Research Comments of the Resea	d to a total depth of 3, 3305.08 set at 3319.2 a crete and 400 sacks not coment was allowed to some with all valves clarilling was resumed. Cities Products	28 and cement. 28 and cement. 320 in lim 320 in l	e. Ran 95 1/10 j ted with 1764 sac Plug was down a casing shut-off a 30 minute peri	t 12:25 P.M. was tested od with no ict Superintend tie) boxe is true and comple dent
This well was drilled OD 32 and 24 casing gel, 110 tacks strate November 19, 1952. With 1000 pound president in pressure. D	d to a total depth of 3, 3305.08 set at 3319.2 a crete and 400 sacks not coment was allowed to some with all valves clarilling was resumed. Cities Products	ction Corpo Company) I hereby certify to the best of my Name	e. Ran 95 1/10 j ted with 1764 sac Flug was down a , casing shut-off , a 30 minute peri	t 12:25 P.M. was tested od with no let Superintend tie) boxe is true and comple dent Corporation